

CLS Control System Progress Report

Elder Matias
Canadian Light Source
University of Saskatchewan
Saskatoon Saskatchewan



EPICS Environment

- EPICS 3.14

– Development: RedHat Linux 7.2

– Servers: RedHat Linux 7.2

- OPI: RedHat Linux 7.2

MS-Windows 2000

- IOC: RTEMS

RedHat Linux 7.2

- PLC: MODICON Momentum

S7/300 or S7/400



- Linac Complete
 - Old CAMAC and NeXT hardware replaced.
 - Modulator control and most vacuum control converted to MODICON Momentum PLC hardware
 - IOC connection: MODBUS over Ethernet
 - Old Power supplies upgraded with single board computers running IOC software.
 - NI FieldPoint used for slow parameters
 - IOC Connection: RS-232



Booster

- Nearly complete
- Vacuum control using MODICON Momentum
- Diagnostics using VME hardware and PowerEdge Server/Linux
- RF Control using S7/300 hardware
 - link to EPICS still under development
- Magnet Power Supplies controlled over RS232



- Storage Ring, Beamlines
 - System Design and Implementation has started
 - Based on similar technologies and design strategies to linac and booster
 - Motor control on beamlines will be based on the CLS standard motor control hardware



Control Room Software


- The Canadian Nuclear Safety Commission requires CLS to conduct detailed task analysis, this activity is driving our operator screen layouts
- EDM has been selected for operator consoles under Linux
- Standard EPICS applications (strip tool, alarm handler etc.) are being used
- Augmented with some customizations or custom applications
- Some specialised applications running under MS-Windows 2000




Services

- HVAC and Cooling Towers with Invensys DMS complete, integration with EPICS postponed
- Secondary Cooling System MODICON
 Momentum and NI FieldPoint complete
- Power Metering/Transformer Control under development
- Cryogenics Plant S7/400 under development











Existing Linear Accelerator

