



# 7-GeV Advanced Photon Source Beamline Initiative



## Conceptual Design Report



Argonne National Laboratory, with facilities in the states of Illinois and Idaho, is owned by the United States government, and operated by The University of Chicago under the provisions of a contract with the Department of Energy.

#### **DISCLAIMER**

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

ARGONNE NATIONAL LABORATORY  
9700 South Cass Avenue  
Argonne, Illinois 60439

---

ANL-93/18 Rev. 1

---

7-GeV Advanced Photon Source  
Beamline Initiative.  
Conceptual Design Report

January 1994

work sponsored by  
U.S. DEPARTMENT OF ENERGY  
Office of Energy Research

## TABLE OF CONTENTS

<b>ABSTRACT</b> .....	1
<b>CHAPTER I BACKGROUND AND OVERVIEW</b>	
1. INTRODUCTION .....	3
1.1 Background .....	3
1.2 Scope of the APS Beamline Initiative .....	4
2. PURPOSE AND JUSTIFICATION .....	4
2.1 Introduction .....	4
3. REFERENCES .....	5
<b>CHAPTER II USER ACCESS AND DEMAND FOR THE ADVANCED PHOTON SOURCE</b>	
1. COLLABORATIVE ACCESS TEAMS .....	7
2. SECTOR ALLOCATION AND DEMAND .....	7
3. LEVERAGING OF CAT RESOURCES .....	8
4. INDEPENDENT INVESTIGATORS .....	8
5. USER COSTS .....	9
6. THE USER SELECTION PROCESS .....	9
6.1 Selection of Collaborative Access Teams .....	9
6.2 Selection of Independent Investigators .....	10
<b>CHAPTER III EXPERIMENTAL FACILITIES</b>	
1. INTRODUCTION .....	13
2. GENERAL LAYOUT OF THE EXPERIMENTAL FACILITIES .....	14
2.1 Introduction .....	14
2.2 Disposition of Beamline Initiative Beamlines .....	14
3. INSERTION DEVICES .....	16
3.1 Introduction .....	16
3.2 Insertion Devices .....	17
3.2.1 Undulators .....	17
3.2.2 Wigglers .....	24
3.2.3 Elliptical Motion Wiggler .....	25
3.2.4 Insertion Device Vacuum Chambers .....	30

## TABLE OF CONTENTS continued

4.	BEAMLINE FRONT ENDS .....	32
4.1	Introduction .....	32
4.2	Description of Front Ends .....	34
5.	STANDARD COMPONENTS OF THE BEAMLINES .....	36
5.1	Introduction .....	36
5.2	Description of Beamline Standard Components .....	36
5.2.1	Filters .....	36
5.2.2	Beamline Windows .....	36
5.2.3	Beamline Slits .....	38
5.2.4	Beam Absorbers and Beam Stops .....	43
5.2.5	Mirror Chambers .....	43
5.2.6	Photon Beam Position Monitors and Supports .....	43
5.2.7	Stepping Motor Drivers and Controllers .....	49
5.2.8	Actuators .....	49
5.2.9	First Optics Enclosures and Experimental Stations .....	49
5.2.10	Supports and Kinematic Mounts .....	49
6.	REFERENCES .....	60

## CHAPTER IV COST AND SCHEDULE

1.	INTRODUCTION TO COST AND SCHEDULE .....	61
2.	COST ESTIMATES .....	63
3.	TIME SCHEDULE .....	67
4.	COST SCHEDULE .....	67

APPENDIX 1	COLLABORATIVE ACCESS TEAM SUMMARIES .....	77
------------	---	----

APPENDIX 2	RESEARCH AND DEVELOPMENT PROGRAM .....	95
------------	--	----

APPENDIX 3	COPY OF SCHEDULE 44 (Jan 1994) .....	101
------------	--------------------------------------	-----

## LIST OF FIGURES

3.2.1	Disposition of sectors at the APS. In the new initiative, Sectors 17 through 20 will be the new sectors .....	15
3.3.1	A comparison of the on-axis brilliance for the APS bending magnet source, Wiggler A, and Undulator A.....	19
3.3.2- 3.3.4	Energy spectra of radiation from Undulator A for three values of K. The positron beam parameters in these calculations are: horizontal beam width $\sigma'_x$ : 308 $\mu\text{m}$ , vertical beam height $\sigma'_y$ : 85 $\mu\text{m}$ , horizontal beam divergence $\sigma'_x$ : 24 $\mu\text{rad}$ , vertical beam divergence $\sigma'_y$ : 9 $\mu\text{rad}$ .....	21
3.3.5	Optimized 2D magnetic flux profile of a quarter period of Undulator A.....	22
3.3.6	Placement of magnetic field components to generate circularly polarized radiation from the elliptical motion of positrons in a wiggler. The $B_x$ and $B_y$ components have a special phase difference of $\pi/2$ along the z axis. In this case, the on-axis radiation is right circularly polarized (Ref. 5).....	26
3.3.7	Conceptual design for the elliptical motion wiggler.....	27
3.3.8	Variation of $P_c$ as a function of photon energy for the elliptical motion wiggler with a period of 15 cm operated at 7 GeV for $K_y=15$ and various values of $K_x$ .....	28
3.3.9	On-axis relative intensity of the circularly polarized beam as a function of photon energy for various values of $K_x$ .....	29
3.3.10	Cross section of the ID vacuum chamber .....	31
3.4.1	Layout of the components of an insertion device beamline front end.....	33
3.5.1	APS beamline filter assembly.....	37
3.5.2	Window for wiggler white beam and wiggler/undulator monochromatic beam .....	39
3.5.3	Monochromatic and white beam dual window .....	40
3.5.4	Bending magnet white beam window .....	41
3.5.5	Differential pump capable of supporting a windowless configuration.....	42
3.5.6	ID white beam horizontal and vertical slits.....	44

## LIST OF FIGURES continued

3.5.7	BM white beam horizontal and vertical slits .....	45
3.5.8	ID monochromatic beam horizontal and vertical slits .....	46
3.5.9	White and monochromatic integral shutters and stops .....	47
3.5.10	X-ray mirror chamber for high power beamlines .....	48
3.5.11	Monochromatic beam position monitor support .....	50
3.5.12	APS heavy load stepping linear actuator .....	51
3.5.13	APS heavy load pneumatic linear actuator .....	52
3.5.14	APS light load stepping linear actuator .....	53
3.5.15	APS light load pneumatic linear actuator .....	54
3.5.16	First optics enclosure .....	55
3.5.17	Experimental station (hutch) .....	56
3.5.18	Support base with precision kinematic mount stages .....	58
3.5.19	Standard support base with standard kinematic mount stages .....	59
4.3.1	APS Beamline Initiative Construction Time Schedule .....	68
4.4.1	APS Beamline Initiative Cost Schedule .....	70
4.4.2	APS Beamline Initiative TEC and TPC Schedule in FY 93 Dollars .....	73
4.4.3	APS Beamline Initiative Budget and Cost Profile .....	75

## LIST OF TABLES

2.1	Status of Collaborative Access Teams (CATs) in the Current Phase (Dec 1993).....	11
3.3.1	Summary of Insertion Devices for Type A Sectors.....	20
3.3.2	Optimized Design Parameters of Nd-Fe-B Hybrid Undulator A.....	23
3.3.3	Partial List of Specifications for Undulator A.....	23
3.3.4	Design Parameters for Wiggler A.....	24
3.4.1	Power and Power Densities Delivered by Various Insertion Devices.....	35
4.1.1	APS Beamline Initiative Work Breakdown Structure.....	62
4.2.1	Cost Account Planning - Direct Cost Estimates.....	64
4.2.2	Craft Codes and Hourly Rates (FY 93\$).....	65
4.2.3	APS Beamline Initiative Cost Breakdown by WBS Code.....	66
4.4.1	APS Beamline Initiative Cost Schedule (FY 93 M\$).....	69
4.4.2	Escalated Rates.....	71
4.4.3	APS Beamline Initiative Cost Schedule (Escalated M\$).....	72
4.4.4	BA/BO Profile (Escalated M\$).....	74
A.1	Effort and Cost for Research and Development Program and Other Project Costs.....	100



# **7-GEV ADVANCED PHOTON SOURCE APS BEAMLINE INITIATIVE CONCEPTUAL DESIGN REPORT**

## **ABSTRACT**

The DOE is building a new generation 6-7 GeV Synchrotron Radiation Source known as the Advanced Photon Source (APS) at Argonne National Laboratory (Project No. 89-R-402). This facility, to be completed in FY 1996, can provide 70 x-ray sources of unprecedented brightness to meet the research needs of virtually all scientific disciplines and numerous technologies. The technological research capability of the APS in the areas of energy, communications and health will enable a new partnership between the DOE and U.S. industry. Current funding for the APS will complete the current phase of construction so that scientists can begin their applications in FY 1996. Comprehensive utilization of the unique properties of APS beams will enable cutting-edge research not currently possible. It is now appropriate to plan to construct additional radiation sources and beamline standard components to meet the excess demands of the APS users. The additional facilities provided by the beamline initiative will lead to additional beamlines, which will be built by Collaborative Access Teams.

In this APS Beamline Initiative, 2.5-m-long insertion-device x-ray sources will be built on four straight sections of the APS storage ring, and an additional four bending-magnet sources will also be put in use. The front ends for these eight x-ray sources will be built to contain and safeguard access to these bright x-ray beams. In addition, funds will be provided to build standard beamline components to meet scientific and technological research demands of the Collaborative Access Teams.

The Conceptual Design Report (CDR) for the APS Beamline Initiative describes the scope of all the above technical construction and provides a detailed cost and schedule for these activities. According to these plans, this new initiative begins in FY 1996 and ends in FY 1999.

The document also describes the preconstruction R&D plans for the Beamline Initiative activities and provides the cost estimates for the required R&D.



# CHAPTER I BACKGROUND AND OVERVIEW

## 1. INTRODUCTION

### 1.1 Background

The 6-7 GeV Synchrotron Radiation Source for the Advanced Photon Source (APS) is now under construction at Argonne National Laboratory (Project No. 89-R-402). This is a synchrotron radiation facility with the unique capability to produce highly brilliant x-ray beams.<sup>1</sup> User groups are now forming to make use of the x-rays from the APS in a variety of research endeavors, from basic science to industrial technology. These groups cover a very wide range of disciplines from condensed matter physics and materials sciences to chemistry and biology, from energy research to pharmaceutical research, from medical research to health sciences research, and from earth sciences to environmental sciences.

The APS facility was planned based on the recommendations by the Eisenberger-Knotek Committee.<sup>2</sup> These recommendations were later studied and endorsed by the Major Materials Facilities Committee of the National Academy of Sciences, chaired by Fredric Seitz and Dean Eastman.<sup>3</sup> The highest priority need for this facility was strongly endorsed by the National Research Council (Brinkman) Committee<sup>4</sup> and by two subcommittees of the DOE Energy Research Advisory Board.<sup>5,6</sup>

Recently, the SEAB Task Force on Energy Research<sup>7</sup> appointed by the Energy Secretary reiterated the above through the following statement: "The Task Force supports the continuation, on the current baseline of cost and schedule, of the Advanced Photon Source (APS) [current phase]. The APS was the highest priority of the 1984 National Academy of Sciences study on major materials facilities, and the Task Force believes that the construction of this third-generation synchrotron facility remains a very high scientific priority for the Department." The DOE's commitment to the construction of the APS is very evident from the funding of its construction, which began in FY 1989.

The current construction phase of the APS will be completed in FY 1997 when the user research programs will begin. However in the current phase of this project, only 32 of the 69 possible x-ray sources will be ready for use. Within the scope of current phase construction, insertion devices and beamline front ends will be built and installed by the APS so that the users can build 32 beamlines on the experiment floor to perform research. The 32 x-ray sources to be completed in the current phase have already been committed to their full use through this century by the scientific and technological users. There are many more users, who could not participate in the current phase, already committing to use the x-ray sources proposed in this Beamline Initiative when they become available. Hence, it is necessary to plan this new initiative to construct the necessary equipment to make the additional x-ray sources functional for user programs. The effective use of the APS will be optimal only when the new construction proposed in this Conceptual Design Report is completed.

In light of the above facts, it is timely to present the APS Beamline Initiative, which proposes the construction to begin in FY 1996 and be completed in FY 1999. The *7-GeV Advanced Photon Source Beamline Initiative Conceptual Design Report (CDR)* presents various elements of this construction project, including the costs and schedules.

## **1.2 Scope of the APS Beamline Initiative**

In the APS Beamline Initiative, 2.5-m-long insertion device x-ray sources, which have been requested by the user groups in their beamline conceptual designs, will be built on an additional four straight sections of the APS Storage Ring. Also, an additional four bending magnet sources will be put to use. The front ends for these eight x-ray sources will be built to contain and safeguard access to these bright x-ray beams.

In addition, the Initiative includes funds for the construction and installation of standard components of the beamline that have personnel and equipment safety implications to the user groups

## **2. PURPOSE AND JUSTIFICATION**

### **2.1 Introduction**

#### Purpose, Justification of Need for, and Scope of Project

The Advanced Photon Source is in great demand by scientific and technological researchers from the fields of physics, materials, chemistry, biology, energy, pharmaceuticals, and medicine. The new Beamline Initiative has two main goals: first, to provide standard beamline components to the technological and academic users forming Collaborative Access Teams; second, to support the unexpected demand for bright x-ray beams by the user community that could not be met in the funded phase of the project.

The APS Beamline Initiative reflects the need for the ultra-bright x-ray beams by industrial and academic users. Applications continue to increase, and they span a wide variety of scientific disciplines, for example, from studies of biological cells to structure of drugs to non-invasive diagnostics of the human heart, from physical sciences to environmental sciences. In order to effectively exploit this national scientific resource, the complement of instrumentation and laboratory space proposed here to support users must be provided.

The importance of this facility for industrial competitiveness of the U.S. is clear. The European countries have jointly built a facility in Grenoble, France, which is similar to the 6-7 GeV Synchrotron Radiation Source being built at Argonne. The Japanese are building a facility in Nishi-Harima that is larger than the APS Project even after the new Beamline Initiative is completed.

The demand for the APS Beamline Initiative reflects unusual research needs for the ultra-bright x-ray beams by industrial and academic users. The applications continue to increase in number with the opening of many unanticipated directions in research, and, as a result, the number of users from different disciplines will increase in the future years.

### 3. REFERENCES

- <sup>1</sup> G. K. Shenoy, P. J. Viccaro, and D. M. Mills, Characteristics of the 7 GeV Advanced Photon Source: A Guide for Users, Argonne National Laboratory Report, ANL-88-9 (1988).
- <sup>2</sup> Planning Study for Advanced National Synchrotron-Radiation Facilities, P. Eisenberger and M. L. Knotek, Chairmen, Sandia Laboratory Report (March 1984).
- <sup>3</sup> Major Facilities for Material Research and Related Disciplines, F. Seitz and D. Eastman, Chairmen, National Academy of Sciences, Washington, DC (1984).
- <sup>4</sup> Physics Throughout the 1990's: An Overview, W. Brinkman, Chairman, NRC Report, National Academy of Sciences, Washington, DC (1986).
- <sup>5</sup> Review of the National Research Council Report on Major Facilities for Materials Research, F. Stehli, Chairman, Energy Research Advisory Board Subcommittee, DOE (1987).
- <sup>6</sup> Review of the National Research Council Report on Physics Through the 1990's, B. Ancker-Johnson, Chairperson, Energy Research Advisory Subcommittee, DOE (1987).
- <sup>7</sup> Report from the Secretary of Energy Advisory Board (SEAB) Task Force on ER Priorities, Charles Towns, Chairman, Washington, DC (1991).



## CHAPTER II USER ACCESS AND DEMAND FOR THE ADVANCED PHOTON SOURCE

The forefront capabilities of the APS will be available to qualified users affiliated with universities, industrial firms, national laboratories, and other institutions. Users may carry out nonproprietary, proprietary, or classified research projects at the APS. Users may participate in research at the APS either as members of Collaborative Access Teams or as Independent Investigators.

### 1. COLLABORATIVE ACCESS TEAMS

Researchers interested in long-term, intensive use of the APS will participate as members of Collaborative Access Teams (CATs). A CAT is an organizational entity that enters into an agreement with the APS, in the form of a Memorandum of Understanding, to develop and operate one or more of the 34 available APS sectors. Each sector consists of an insertion-device (ID) beamline and an adjacent bending magnet beamline. CATs are selected by means of a proposal process, which is described in Section 6 of this chapter (*The User Selection Process*). Each CAT will use its own funds to develop its sector(s), that is, to design, construct, and install the scientific equipment and optics required for their research on the beamlines that will be located outside the concrete shielding tunnel. The APS will design, construct and install some of the standard components of the beamline that have direct impact on the personnel and equipment safety. A group may request multiple sectors, with the understanding that it will develop them simultaneously. The APS assists in forming associations among groups requiring less than one sector to create larger groups whose combined needs justify the use of a whole sector.

CATs can be organized along disciplinary or institutional lines, or as multi-institutional consortia. Typical sponsors for CATs include academic institutions, national laboratories, industrial firms and consortia, governmental bodies, synchrotron service companies, or combinations of the above categories. In addition, a CAT can be established to operate one or more sectors as a national user facility in support of a specific discipline.

Each CAT will appoint a director, who will assume line responsibility for managing beamline development, operation, and safety. The APS will approve the CAT safety plans and will retain the ultimate responsibility for safety.

### 2. SECTOR ALLOCATION AND DEMAND

The first step in the sector allocation process is the consideration of proposals submitted to the APS by prospective CATs. The elements of a CAT proposal and the process by which it is submitted and reviewed are described in Section 6 of this chapter (*The User Selection Process*). In Table 2.1, the status (as of May 1993) of the Collaborative Access Teams (CATs) formed by the APS users is given. The number of CATs approved by the APS Proposal Evaluation Board (PEB) is 15, and several more CATs have received provisional approval. These 15 CATs are in need of 19 APS sectors to build 38 beamlines. On the other hand, the APS will develop only 16 sectors where users group can build 32 beamlines. At this time, the additional requests for 6 beamlines by the APS user groups can only be accommodated in the new APS Beamline Initiative presented in this document. Experience indicates that this demand will only grow during the coming years. Collectively, the approved CATs encompass more than 500 principal investigators from about 72 universities, 28 industrial firms, 18 national or private research laboratories, and 8 medical schools.

Appendix 1 gives information about the research focus and institutional makeup of the 15 approved CATs.

Each CAT with an approved proposal submits a Conceptual Design Report (CDR) to the APS for review by an independent Instrumentation Feasibility Panel. The CDR describes in detail the beamline components (outside of the concrete shielding tunnel) needed to carry out the research mission of the CAT. These components, which the CAT will furnish, include the first optics, beamline optics, and experimental equipment. Information provided in the CDR relative to these components includes spectral requirements, conceptual optical and mechanical designs, and R&D requirements.

Once a CAT has both an approved CDR and an approved plan for sector management, as well as written statements of funding intent from the organizations it has identified as its sources of financial support, the CAT and the APS will sign a Memorandum of Understanding (MOU). The MOU specifies the number of sectors allocated to the CAT and the length of its initial period of tenure. A separate document, *APS User Policies and Procedures*, will give details of the working relationship between the CATs and the APS during the sector development and operation phases.

### **3. LEVERAGING OF CAT RESOURCES**

The APS will equip all sectors (whether allocated to a CAT or not) with bending magnets because these are essential to the operation of the Storage Ring. In addition, the APS will equip as many sectors as possible, subject to the availability of funds, with the remaining instrumentation needed behind the concrete shielding tunnel to support two beamlines per sector. This additional instrumentation consists of a general-purpose 2.5-m-long ID, and the front ends for the ID and bending-magnet beamlines. In the initial phase of this effort, the APS expects to be able to equip 16 of the 34 available sectors behind the concrete shielding tunnel. Through this Beamline Initiative funds are sought to equip an additional four sectors in this manner.

To reduce beamline design and construction costs for the CATs, the APS has undertaken to identify beamline components that can be standardized, to develop engineering designs and prototypes of such components, and to share these designs and cost estimates with the CATs. An independent Beamline Standardization and Modularization Committee has contributed to this effort. Also, the APS is implementing an on-line Design Exchange to allow CATs and the APS to share drawings of beamline components and layouts. In the current Beamline Initiative, funds will be set aside to provide many of the standard components to the CATs, especially those components that have significant personnel and equipment safety implications.

### **4. INDEPENDENT INVESTIGATORS**

Groups and individuals interested in independent access to the APS are an equally important part of the user community, and the APS is committed to providing these "Independent Investigators" with the beam time needed for successful scientific programs. Therefore, CATs must allocate an agreed-upon percentage of their beam time to Independent Investigators, whom the CATs will select by means of a proposal process (see Section 6.2). In general, the fraction of CAT beam time allocated to Independent Investigators will be 25%; it may be higher for CATs seeking more equipment support from the APS. The actual requirement for allocating the Independent Investigator beam time will be agreed upon on a case-by-case basis. Each CAT will prepare a written description of the facilities to be available for the use of Independent Investigators and will do its own scheduling and beamline-specific safety training of Independent Investigators.

Independent Investigators will follow the procedures specified by the host CAT for using beamline and experimental equipment and will perform all work in accordance with the same safety

and procedural standards that apply to CAT members. Independent Investigators will provide the CAT with accurate and accessible records that identify the users present and the experimental work to be conducted during each assigned shift. They will also provide the CAT with copies of any publications that result from their use of the APS.

## **5. USER COSTS**

All CATs will be fully responsible for obtaining funds to design and build their beamlines, beyond what the APS will provide to them as described above. Once operations begin, users will not be charged for base operating costs, such as maintenance and utility costs for the Experiment Hall, nor for beam time used to do research that will be published in accessible literature. In accordance with U.S. Department of Energy policy, users (CATs or Independent Investigators) doing proprietary research will reimburse the APS for beam time at the full cost recovery rate. All users will reimburse the APS for incremental goods and services such as stockroom purchases, computer time, and telephone and shop services.

## **6. THE USER SELECTION PROCESS**

### **6.1 Selection of Collaborative Access Teams**

CATs are selected by a two-step process involving submission of (1) letters of intent and (2) full proposals from teams whose letters of intent are approved. Letters of intent are welcome from groups requiring one or more sectors as well as groups requiring less than a whole sector.

A Proposal Evaluation Board (PEB), consisting of six distinguished scientists, has been established in consultation with the APS Users Organization Steering Committee (elected representatives of prospective APS Users). The PEB evaluates the scientific merit of letters of intent submitted by prospective CATs; CATs whose letters are approved are invited to submit full proposals. Each proposal is reviewed by the PEB with input from a Scientific Review Panel with expertise in the relevant discipline(s). The PEB then makes recommendations to APS management, which has the final responsibility for CAT selection.

#### **6.1.1 Submitting a full proposal**

The content requirements for proposals, along with a description of the review process and a generic Management Plan, are given in *Guidelines and Forms for Proposals to Develop Collaborative Access Teams at the Advanced Photon Source* (Advanced Photon Source, November 1990). The major elements of a CAT proposal are as follows:

- objectives of the proposed research, and the approaches to be taken in meeting those objectives,
- description of the role of each CAT member,
- preliminary conceptual designs of the beamlines, including a feasibility analysis, cost estimate, and construction timeline,
- strategy for obtaining funding, and
- preliminary CAT Management Plan, including an organization chart, work breakdown structure, QA/QC plan, component procurement/fabrication plan, cost/schedule/performance control plan, and safety plan.

#### **6.1.2 Proposal review**

In evaluating CAT proposals, the PEB again considers the scientific and technical merit of the proposed research and the degree to which it will use the forefront capabilities of the APS. For

each proposal, the PEB receives substantial input from one of several Scientific Review Panels and from additional independent reviewers with expertise in the specific areas of interest. Also considered are the probability of accomplishing the stated objectives, the qualifications and experience of the CAT members, the feasibility of the beamline design, and the adequacy of the financial strategy and plan for sector management. In addition, an attempt is made to balance the proposals selected for approval so that a number of scientific disciplines are represented at the APS.

## **6.2 Selection of Independent Investigators**

Prospective Independent Investigators will submit proposals directly to CATs that are operating suitable beamlines. Independent Investigators will be encouraged to submit their proposals to multiple CATs, with the order of preference indicated. The APS will act as a clearinghouse in this process and will screen the proposals to ensure that safety issues are appropriately addressed.

The designated CATs will either use their own APS-approved proposal review process or forward the proposals to a review committee established under APS auspices. The APS will monitor the overall process to ensure that the requirements specified in each CAT's Memorandum of Understanding are met.

Table 2.1

Status of Collaborative Access Teams (CATs) in the Current Phase  
(Dec 1993)

---

Letters of Intent Reviewed/Approved	35/22
CAT Proposals Reviewed by the PEB	20
CAT Proposals Approved	15
New Proposals under Preparation	5
APS Sectors Requested	22
Sectors Approved	20
Sectors Requested by the New Proposals	5
Sectors To Be Instrumented behind Shield Wall in Current Construction	16
Total Principal Investigators	500
Number of Universities	72
Number of Industries	28
Number of Government and Private Labs	18
Number of Medical Schools	8
Approximate Cost of Construction of Proposed Beamlines	\$182 M
Funds Committed by Industries	\$ 22 M
Funds Assured by DOE/NSF/Federal and Non-Federal Agencies	\$ 76 M

---



## CHAPTER III EXPERIMENTAL FACILITIES

### 1. INTRODUCTION

In this section, a brief description of the experimental facilities is provided.

There are 40 straight sections on the Advanced Photon Source storage ring, of which 34 will be available for the use of insertion devices. The remaining six sections are reserved for the storage-ring hardware and diagnostics. The storage ring incorporates 80 bending magnets; however, only 35 will be available for extracting radiation beams. One set of a bending magnet radiation port and an insertion device (ID) radiation port constitutes a sector.<sup>1</sup>

Generally, the ID photon beamline consists of four functional sections. The first section is the ID (or IDs) on a single straight section that provides the radiation source(s). In the case of a bending magnet beamline, the radiation is produced by the bending magnet.

The second section, immediately outside the storage ring but still inside the concrete shielding tunnel, is the front-end section of the beamline. This section contains the masks, apertures, safety shutters, photon beam position monitors, filters, window, etc., which confine, define, and control the photon beam.

The third and the fourth sections of the beamline are usually built by the user groups to their requirements but are suitably designed to meet all the APS safety and design requirements. In the third section, just outside the concrete shield wall and on the experiment floor, is the first optics enclosure (FOE). In a majority of experiments, the FOE contains optics for delivering filtered or monochromatic radiation. The crystal and/or mirror and/or multilayer optics contained in the FOE are designed to handle the expected radiation power loads from either the IDs or the bending magnet source. In a few cases, the FOE may be used to carry out white radiation experiments.

The fourth section of the beamline will vary widely depending on the nature of the investigations. Generally, it consists of beam transport, additional optics, apertures, filters, and, finally, the experimental station. This station contains the sample under investigation, radiation analyzer optics, detectors, etc., to characterize the scattering, imaging, or absorption processes. The experimental station will also contain various instruments to control the environment of the sample under study.

Typically, the third and the fourth sections of the beamline will occupy the experiment floor, which allows for a maximum of about a 70-m-long beamline measured from the center of the ID straight section. Some applications will require much longer beamlines, extending out of the Experiment Hall. Such beamlines will require additional buildings located outside the Experiment Hall to support the instrumentation and data collection. There are at least two locations to place long beamlines (200 m to 1000 m) that could extend beyond the Experiment Hall without any building obstructions.

In all, there can be at least 34 ID beamlines and 35 bending magnet beamlines on this facility, assuming that only one section 3 and one section 4 is built on each of the radiation sources.

In the current construction phase of the APS project, funds are provided to develop sections 1 (insertion device) and 2 (front end) of the beamlines in 16 sectors. As described in Chapter II, at the present time, the number of user proposals for APS sectors exceeds 16 (16 ID and 16 bending

magnet). Hence, an additional four sectors are included in this initiative. These sectors also are to be equipped behind the shield wall. The present initiative also includes construction of many standard components of sections 3 and 4 of the beamline that have safety implications and so are best supplied by the APS to the users. The user groups are raising funds to build instrumentation in sections 3 and 4 that are directly related to the scientific goals of each of the CATs in all the proposed sectors.

In this chapter (Chapter III), the scope and conceptual design for the experimental facilities of the new initiative will be provided. The reader should be reminded that most of the experimental facilities included in this initiative are often duplicated from the current construction phase. Hence, these components have been designed in various degrees of detail at this time and will be going through complete Title II engineering design review before the end of fiscal year 1993. It should also be pointed out that in estimating the ED&I costs for the experimental facilities to be provided in the Beamline Initiative, only those costs that are not covered by the design work in the current phase are included in addition to Inspection (I) costs.

## **2. GENERAL LAYOUT OF THE EXPERIMENTAL FACILITIES**

### **2.1 Introduction**

The APS Beamline Initiative intends to extend the experimental facility on the APS by installing equipment behind the shield wall (IDs and front ends) in four additional sectors. It also includes funds for beamline standard components that have been identified by the user groups. Many of these components have significant safety implications and, hence, are best built under the design and construction supervision of the APS. It should be understood that the exact nature of these standard components to be placed in the various CAT beamlines will be specified in the detailed beamline designs from each of the CATs, and these individual beamline designs will define all the safety requirements.

### **2.2 Disposition of Beamline Initiative Beamlines**

The beamlines in the current construction project occupy the following 16 sectors: 1 through 8 and 13 through 20 (see Fig. 3.2.1). The set of insertion devices that will support these beamlines will include planar undulator and wigglers. These devices are typically 2.5 m long, and the currently designed front ends are capable of handling the power and power density from such devices.

In the new initiative, there are many users who will design their beamlines based on the above set of insertion devices and supporting front ends. There will be four more such sectors, that will be built in the APS Beamline Initiative. This brings the total number of sectors to 20. The placement of the new sectors on the experiment floor is likely to occupy Sectors 9 through 12 (see Fig. 3.2.1).

It is clear that most CATs would like to concentrate on designing specialized equipment related to their scientific programs rather than on routine or standard beamline components. The components such as the beam transports, first optics enclosure, and experimental stations require substantial safety-related engineering. Hence, these components will be built by the APS through the funding from this initiative so that there is uniform application of all DOE safety standards through out all the user beamlines. Identifying standard components is a nontrivial task because these components should support diverse beamline objectives. To assist this effort, the APS has obtained advice and help from a Beamline Standardization and Modularization Committee made up of experts in beamline design, construction and operation. This Committee




Fig. 3.2.1 Disposition of sectors at the APS. In the new initiative, Sectors 17 through 20 will be the new sectors.

has worked with the APS during the past three years and has specified the beamline standard components. Many of the CATs have recently participated in the deliberations of this Committee to contribute to the standard beamline component design process.

### 3. INSERTION DEVICES

#### 3.1 Introduction

The Advanced Photon Source will be a powerful source of high-brilliance hard x-rays with energies above 1.0 keV. In addition to the availability of bending magnet (BM) radiation, which has a critical energy of 19.5 keV, undulator and wiggler insertion device (ID) sources can be introduced on 34 straight sections on the storage ring. The unique spectral properties and expected flexibility in the ID operation will support the APS users in the current construction phase. Proposed new techniques utilizing the full potential of ID sources will be the focal point of research for many users.

In most of the APS sectors, the IDs are composed of two sets of magnet arrays in a planar geometry that produce a spatially oscillating magnetic field along the length of the device. The arrays are typically made of permanent magnets with high permeability magnetic poles.

The spectral properties of the devices are related to the peak magnetic field,  $B_0$ , in the mid-plane of the two arrays in a planar ID. The resulting amplitude of oscillating motion of the particle beam and the maximum slope angle of the trajectory depend linearly on both  $B_0$  and the period of the device,  $l_0$ , through the deflection parameter,  $K$ , defined by

$$K = 0.933 l_0 \text{ (cm)} B_0 \text{ (Tesla)}.$$

For  $K$  less than approximately ten, the maximum slope angle is  $\theta = K/\gamma$ , where  $\gamma = 13699$ , the relativistic mass enhancement for the 7-GeV positron. This is to be compared with the natural opening angle of synchrotron radiation,  $\psi \approx 1/\gamma$ , which is approximately 73  $\mu\text{rad}$  for the 7-GeV APS storage ring.

The spectral properties of a planar device will depend on the relative values  $\theta$  and  $\psi$ . In the undulator regime, where  $K \approx 1$ , the radiation from each part of the trajectory is within the radiation opening angle  $\psi$ . This results in spatial and frequency bunching that gives rise to a typical undulator spectrum consisting of narrow energy bands of radiation called harmonics. The energy of the harmonics is dependent on the energy of the positron and the magnetic field experienced by the positron. Typically, the radiative divergence at the harmonic energy is a fraction of the natural opening angle,  $\psi$ , and the photon density at this energy is enhanced.

In a planar wiggler, where  $K \geq 5$ , the output from the device is the sum of intensities from each magnetic pole, and the spectral output is similar to that from an equivalent BM but is contained within a horizontal angular range of  $\pm K/\gamma$ . The spectral output on axis is approximately  $N$  times the output from an equivalent BM source, where  $N$  is number of magnetic poles in the wiggler.

The spatial and angular distribution of the 7-GeV positron beam will affect the undulator spectrum most severely. Because the positrons in the beam are independent, the effective source

size and angular distribution are a convolution of the radiative and particle beam distribution parameters.

The capability to design IDs that can provide x-rays with different polarization properties is as yet a new area, which will be exploited in the APS Beamline Initiative. During the past year, the APS has added polarization insertion devices to its standard list because some of the CATs have requested them. Hence, as a part of this initiative such devices will be built. These complex insertion devices are generally made up of four magnet arrays providing the oscillatory field in the x and y directions. In these IDs, the magnetic field vector experienced by the positron moving in the z direction is given by

$$\mathbf{B} = \mathbf{e}_x B_{x0} \cos(2\pi z/\lambda_0) \pm \mathbf{e}_y B_{y0} \sin(2\pi z/\lambda_0),$$

and the deflection parameter is given by

$$K_{x,y} = 0.933 B_{x0,y0} \lambda_0.$$

Based on the values of  $K_x$  and  $K_y$ , the positron will move with relativistic velocities either in a helical or an elliptical trajectory. Hence, depending on the relative values of  $K_x$  and  $K_y$ , one can generate undulator or wiggler radiation with different polarization contents.

### 3.2 Insertion Devices

Three IDs have been identified as standard x-ray sources. These include one planar undulators and two wigglers.<sup>2</sup> Undulator A, which has Nd-Fe-B permanent magnets and vanadium permendur poles to form a hybrid geometry, is capable of spanning the photon energy interval from 4.7 to about 40 keV using the first- and third-harmonic radiation. Wiggler A, with a hybrid magnet geometry and a critical energy ( $E_c$ ) of 32.6 keV, and an elliptical motion wiggler, with a magnetic structure based on permanent magnet and electromagnets and a critical energy of 31 keV, have been designed. These critical energies are well above the 19.5 keV for the bending magnet radiation. Figure 3.3.1 shows a comparison of the on-axis brilliance of the BM source to that of the Wiggler A and Undulator A sources.

#### 3.2.1 Undulators

The design parameters for Undulator A have been well developed and design work is beyond the Title II phase. As a part of the study, Monte-Carlo simulations of the radiation properties of these IDs have been performed.<sup>3</sup> A summary of the properties of these IDs is given in Table 3.3.1. Figures 3.3.2-4 show the energy spectra of radiation from Undulator A for three values of  $K$ . Such devices are now being procured as part of the current construction phase.

The planar geometry of this undulator has a hybrid configuration in which the magnetic field strength and distribution depend on the geometry of the pole tips. The field quality is also determined by the magnetic and geometric quality of the magnetic material. In arriving at the magnetic structure of this device, various geometric parameters of the structure are iteratively optimized through a two-dimensional field computation (yz plane). The resulting parameters are presented in Table 3.3.2. Three-dimensional (3D) effects are estimated in order to obtain a pole width and a magnet width that provide the required field homogeneity.

Figure 3.3.5 shows the optimized two-dimensional magnetic flux lines of a quarter period of the 3.3-cm-period undulator at gaps of 1.15 and 3.00 cm. The pole piece has been chamfered at

45° to avoid both flux saturation at the corners of the pole tip and the demagnetization of the permanent magnet material.

Undulator A will support the special needs of the user community, namely, the capability to generate "broad-band" undulator radiation. This is accomplished by tapering the two magnetic arrays of a planar undulator along the z axis. This concept has already been tested by the APS Experimental Facilities staff and will be incorporated in all the devices constructed.

The undulator assemblies have magnetic field end-correctors. A detailed analysis of the geometry of the end-correctors has been experimentally evaluated as a part of the R&D program. This has provided a solid basis for providing the end-corrector design and the pole width specification.

In Table 3.3.3, partial specifications for the periodic magnetic structure of Undulator A are presented. These specifications assure sufficient dynamic aperture for the storage-ring lattice to provide its optimal performance.

As a part of the design activity in the current phase, Undulator A has now been fully specified with regard to its design tolerance requirements. A number of Undulators A are being procured during FY 1993-94 to complete the current phase construction and will be commissioned and operated during FY 1995-96. This experience should greatly enhance our capability to build the undulators in the APS Beamline Initiative.








Figure 3.3.1 A comparison of the on-axis brilliance for the APS bending magnet source, Wiggler A, and Undulator A

Table 3.3.1  
Summary of Insertion Devices for Type A Sectors


	Undulator	Wiggler
	A	A
Period (cm)	3.3	8.5
Number of Periods	72	28
Length (m)	2.4	2.4
Undulator 1st-Harmonic		
Minimum (keV)	4.2	
Maximum (keV)	14	
Wiggler Critical Energy		
$E_c$ (keV) at 2.2 cm gap		32.5
$K_{max}$	2.17	13.4



Figures 3.3.2 - 3.3.4 Energy spectra of radiation from Undulator A for three values of  $K$ . The positron beam parameters in these calculations are: horizontal beam width  $\sigma'_x$ : 308  $\mu\text{m}$ , vertical beam height  $\sigma'_y$ : 85  $\mu\text{m}$ , horizontal beam divergence  $\sigma'_x$ : 24  $\mu\text{rad}$ , vertical beam divergence  $\sigma'_y$ : 9  $\mu\text{rad}$



Gap: 11.50 mm



Gap: 30.00 mm

Figure 3.3.5 Optimized 2D magnetic flux profile of a quarter period of Undulator A

Table 3.3.2  
Optimized Design Parameters of Nd-Fe-B Hybrid Undulator A

Undulator A	
Undulator Period (cm)	3.3
Magnet Gap	
Minimum (cm)	1.15
Maximum (cm)	3.0
Pole Width- x Direction (cm)	6.00
Pole Height - y Direction (cm)	6.0
Pole Thickness - z Direction (cm)	0.56
Magnet Width - x Direction (cm)	7.80
Magnet Height - y Direction (cm)	6.85
Magnet Thickness - z Direction (cm)	1.10
Pole Tip Overhang - y Direction (cm)	1.00
- x Direction (cm)	0.90
Peak Field on Axis - Maximum (G)	6917

Table 3.3.3  
Partial List of Specifications for Undulator A

Parameter	Specification
Maximum Random Field Error (%)	0.48
Gap Resolution ( $\mu\text{m}$ )	2.5
Transverse Roll-Off at $\pm 1$ cm (%)	0.5
Total Steering Errors (G-cm)	<100
Normal Components of:	
Integrated Quadrupole (G)	<50
Integrated Sextupole (G/cm)	<200
Integrated Octupole (G/cm <sup>2</sup> )	<300

### 3.2.2 Wignlers

The prerequisite for wignlers is a large K value, which will result in a continuous and wide energy spectrum. This is achieved by having either a large  $B_0$  and/or a large  $\lambda_0$ . The critical energy of the spectrum can be made either large or small by the proper choice of peak magnetic field. In Table 3.3.4, design parameters for APS Wignler A are given.

The Title II design of this device is complete, and it will be procured for the current construction phase before the end of FY 1993. The experience gained in this process and in installation and commissioning during FY 1994-95 will be of great benefit during the Beamline Initiative.

Table 3.3.4  
Design Parameters for Wignler A

Parameters	Wignler A
Peak Field on Axis (G) at 1.15 cm gap	1690
Peak Field on Axis (G) at 2.2 cm gap	1000
Period (cm)	8.5
Kmax	14
Number of Periods	28
Length (m)	2.4
Critical Energy (keV) at 2.2 cm gap	32.6
Structure	Nd-Fe-B
Flux at Critical Energy $10^{14}$ (ph/s/0.1%BW/mrad)	8.0

### 3.2.3 Elliptical Motion Wiggler

A new insertion device requested by the users is the elliptical multipole wiggler. The principle of such a device is illustrated in Fig. 3.3.6, and a conceptual configuration is shown in Fig. 3.3.7. This wiggler consists of one set of magnet arrays that produces a large vertical magnetic field ( $B_y$ ) and a second set of magnet arrays that produces a small horizontal field ( $B_x$ ). The two fields  $B_x$  and  $B_y$  are  $\pi/2$  out of phase. The resulting field is helical with different radii in the horizontal and vertical planes. When  $K_y \gg 1$  and  $K_x \approx 1$ , the on-axis radiation is circularly polarized. The radiation is effectively a superposition of the off-plane radiation from a bending magnet source because half the period of the positron orbit can be regarded as the orbit through the bending magnet. The intensity of the on-axis radiation from such a wiggler is  $2N$  times higher than that from a bending magnet,  $N$  being the number of periods in the wiggler.

The choice of  $K_x$  is crucial for generating both a high degree of polarization,  $P_C$ , and high brightness. Large values of  $K_x$  will lead to a nearly unit value for  $P_C$ ; however, in that case, the on-axis brightness will be small. The elliptical multipole wiggler to be built in the APS Beamline Initiative will have  $K_y \approx 15$  and  $K_x \approx 1$ . With  $\lambda = 15$  cm, such a device will have a critical energy of about 32 keV and a  $P_C$  value of about 0.9 over a wide energy range. In Fig. 3.3.8, the variation of  $P_C$  as a function of photon energy for this device is shown for various values of  $K_x$ . The on-axis relative intensity of the circularly polarized beam as a function of photon energy for various values of  $K_x$  is shown in Fig. 3.3.9.<sup>4</sup>  $K_x$  will be chosen depending on the nature of the experiment. A device of this type has been tested on the Accumulator Ring at TRISTAN.<sup>5</sup>

It is equally important to note that the value of  $P_C$  can be degraded by the vertical beam divergence  $\sigma_y'$ , or by large experimental angular acceptance,  $\theta$ . To minimize such degradations, the following equation should be satisfied:

$$K_x > \gamma[\sigma_y'^2 + (\theta/2)^2]^{1/2}.$$

Use of pinholes placed along the beamline can achieve  $\theta \ll \sigma_y'$ . For the APS,  $\gamma \sigma_y'$  is 0.12, and, hence, the above condition is easily satisfied for all values of  $K_x > 0.2$ .

The translation of the set of x-magnet arrays relative to y-magnet arrays in this device will produce different states of polarization. For example, if the two sets of magnet arrays are in phase, linearly polarized radiation will be produced. On the other hand, if the phase angle between the two sets of magnet arrays is either  $+\pi/2$  or  $-\pi/2$ , the on-axis radiation will be either right or left circularly polarized. The phase change can be accomplished by translating the horizontal magnet array from  $-\lambda/4$  to  $+\lambda/4$ .

The ability to switch between various polarization states in a single investigation will be of considerable importance. This switching would demand the translation of one set of magnet arrays relative to the other set along the z direction. However, it is difficult to accomplish such mechanical movements on a short time scale because of strong magnetic interactions between the two sets of magnet arrays. One way of switching the state of polarization is by employing electromagnets in the horizontal magnet arrays. Such a device will be capable of switching the circular polarization state between right- and left-handedness within milliseconds. The design of the horizontal electromagnetic arrays will need detailed considerations on reducing eddy currents.




Figure 3.3.6 Placement of magnetic field components to generate circularly polarized radiation from the elliptical motion of positrons in a wiggler. The  $B_x$  and  $B_y$  components have a special phase difference of  $\pi/2$  along the z axis. In this case, the on-axis radiation is right circularly polarized (Ref. 5)




Figure 3.3.7 Conceptual design for the elliptical motion wiggler




Figure 3.3.8 Variation of  $P_C$  as a function of photon energy for the elliptical motion wiggler with a period of 15 cm operated at 7 GeV for  $K_y = 15$  and various values of  $K_x$




Figure 3.3.9 On-axis relative intensity of the circularly polarized beam as a function of photon energy for various values of  $K_x$

A prototype of this device is being designed during FY 1993 and will be operated at the NSLS during FY 1994-95.

### 3.2.4 Insertion Device Vacuum Chambers

The ID vacuum chamber provides a straight section continuum of the storage ring enabling the positron beam to pass through the mid plane of the ID. The trajectory of the beam through the ID results in an intense x-ray beam. The straight section ID vacuum chamber requires a vacuum level of  $10^{-10}$  Torr, similar to that of the storage ring. Poorer vacuum can result in unacceptably high production of bremsstrahlung radiation from the scattering of the positron beam from gas molecules.

The design of the vacuum chambers has received considerable attention during the current phase design studies. The tolerance specifications are a very critical element of this design study. Prototype chambers have been built and tested as part of the current phase R&D studies, and the information obtained will provide the necessary input for the Beamline Initiative construction activities.

The overall length available in each sector of the storage ring for the ID vacuum chamber is 4.8 m. This length excludes the transition section between the storage ring vacuum chamber and the ID chamber. Because the devices will generally be 2.4 m long, in the final design the length of ID vacuum chamber may be limited to this length with the remaining part of the straight section being occupied by the standard storage ring vacuum chamber.

The ID vacuum chamber has a cross section that is considerably smaller in dimension than that of the main storage ring chamber. A cross-sectional view of such a chamber is shown in Fig. 3.3.10. The ID chamber consists of an elliptical positron beam chamber connected to a pumping antechamber (containing NEG strips) through a narrow channel. The material of choice for the chamber is a 6063-T5 aluminum alloy, and the geometry is achieved through an extrusion process.

The positron beam chamber is situated in the mid-plane region of the upper and lower magnet arrays of the ID. The maximum magnetic field developed by the ID magnets depends on the minimum gap. This gap over the length of the ID and its dimensional tolerance determine the maximum magnetic field achievable for an ID. For reasons of energy tunability, it is desirable to reach the largest field possible at the minimum gap. For the ID chambers to be installed in the APS Beamline Initiative, the nominal minimum dimension of the positron beam chamber is 10 mm. A detailed analysis of various mechanical tolerances leads to a total tolerance budget of 1.5 mm for the vacuum chamber and its supporting structure. With the manufacturing technologies available, this tolerance should be easily achievable. This ID vacuum chamber will lead to a minimum magnetic gap of 1.15 cm for the ID, which fully supports the spectral requirements from all the insertion devices.




Figure 3.3.10 Cross section of the ID vacuum chamber

## 4. BEAMLINE FRONT ENDS

### 4.1 Introduction

The front end of a beamline has specific functions. These have been defined for the current phase beamline front ends, and the principal functions are listed below:

- maintain the storage-ring vacuum integrity,
- confine the photon beam power to safeguard all front end and beamline components,
- maintain adequate capability to handle the largest power and power density on front end components,
- ensure personnel safety with triple redundancy and logical control systems during both the commissioning and operating phases,
- provide required information on the angular and spatial position of the photon beam to keep it to a specified stability.

In the current phase construction, 32 front ends will be built; 16 of these will be on the ID beamlines and the remaining 16 will be on the BM beamlines. APS IDs include both wigglers and undulators, and the properties of the radiation produced by these devices will vary. However in the current construction phase, ID front ends are designed to handle the radiation from all the proposed devices.

A layout of the front-end components for an ID beamline is shown in Fig. 3.4.1. Starting from the source end, the following components are identified:

Exit Valve - An all-metal valve that isolates the front end from the storage ring. Opening this valve is controlled administratively. It is open when the ID is operational.

Photon Beam Position Monitor (photon BPM) - A system capable of detecting the position of the beam both in the x and y directions without interfering with the central part of the beam. In combination with a second photon BPM placed 5-7 m downstream, it specifies the precise angular and spatial location of the beam. Photon beam missteering is controlled to within 10% of its angular and spatial size with a feedback loop to correction magnets in the storage ring that adjust the position and angle of the positron beam.

Fixed Mask (Aperture) - A vertical and/or horizontal set of cooled plates that confine the beam to a defined size and admit radiation into downstream components.

Collimators - These components define the line of sight to the source point and admit a cone of radiation. Portions of the beam outside the predefined cone, scattered x-rays, and the bremsstrahlung radiation are absorbed by the collimator body.

Slow Valve - An all-metal, remotely actuated, non-cooled UHV valve that seals to isolate the storage ring vacuum from any vacuum breach in the downstream transport.

Fast Valve - A very fast acting valve, non-cooled, that retards the shock wave progression upstream in case of a vacuum breach in the downstream components.



Filters - Typically, cooled pyrolytic graphite or diamond foils to absorb and dissipate heat from unwanted spectral portions of the photon beam.

Safety Shutters (Injection Stops) - High-Z, metal-based safety blocks, usually in tandem, that absorb bremsstrahlung radiation produced during cold fills of the positron beam into the storage ring.

Window - A vacuum separator that isolates the vacuum of the front end and the storage ring from that of the beamline on the experiment floor. This window (located outside the shield wall) allows the transmission of the photons to the experiment. A differential pumping system has been developed to replace the window when low energy radiation is to be delivered to the experiment.

A detailed logic has been developed with the required redundancy to provide personnel safety in the operation of all the components of the front end. The BM front end has basically the same set of components. The capability to handle the power delivered by various radiation sources is crucial to the final design of all the front-end components. Currently, R&D and testing of prototypes of various front-end components are underway to meet the demands of the radiation sources proposed. The procurement of front end components required for the current phase will begin in FY 1993, and the components will be installed and commissioned during FY 1994-95. This should assure timely implementation of front ends for four IDs and four BM sources in the Beamline Initiative.

#### **4.2 Description of the Front Ends**

A detailed discussion of the angular dependence of the radiation power from the insertion device sources and bending magnet source can be found in the current phase Design Handbook. The crucial number is the peak power density normal to the surface at a specified distance from the source where the various front-end components will be located. The total power from the IDs is equally important in the design of the front-end components. Many measures are being implemented in the front-end design, first, to reduce the power and, second, to handle the power. In arriving at the engineering designs of the components of the front end, extreme care is taken to select the best heat transfer methodology, material properties, stress reduction methodology, etc.

Because of the large power densities involved, front-end components such as masks or shutters cannot be placed at normal incidence to the ID radiation beam, regardless of how efficiently they are cooled.

In Table 3.4.1, the power densities and powers delivered by various IDs are given.

Table 3.4.1  
Power and Power Densities Delivered  
by Various Insertion Devices <sup>a</sup>

	Undulator A	Wiggler A	Elliptical Wiggler
Device Length (m)	2.5	2.5	2.5
Maximum Field (T)	0.8	1.0	1.0
Total Power (kW)	5.0	4.6	7.8
Peak Power Density <sup>b</sup>	150	26	42
Peak Flux @ 16 m <sup>c</sup>	0.59	0.10	0.16
Peak Flux @ 24 m <sup>c</sup>	0.26	0.05	0.07

<sup>a</sup> The current in the storage ring is assumed to be 100 mA.

<sup>b</sup> Units are (kW/mrad<sup>2</sup>)

<sup>c</sup> Units are (kW/mm<sup>2</sup>)

## **5. STANDARD COMPONENTS OF THE BEAMLINES**

### **5.1 Introduction**

In this section, current plans for building the standard components of the beamlines in the APS Beamline Initiative are presented. It has been pointed out earlier that the standard components of the beamlines have been identified and specified using the input from the Beamline Standardization and Modularization Committee and members of the CATs. There are many safety considerations for such components. They include radiation shielding requirements for synchrotron radiation from various planned insertion devices and the bremsstrahlung, ALARA design objectives, and interlocks with adequate visual and audible alarms compatible with the APS control system. The exact complement of standard components that will be built will be decided after reviewing all the CAT beamline designs. At this time, the conceptual designs of these CAT beamlines are being reviewed. The Title I designs of the CAT beamlines will be reviewed by the APS during FY 1993, and this process will lead to the standard components that the APS will build under this new initiative.

In a separate document, *APS Beamline Standard Components Handbook*, all the standard components have been specified. This document is regularly updated to include new input from the users. As a part of this activity, the beamline vacuum and shielding requirements have been specified in detail.

### **5.2 Description of Beamline Standard Components**

#### **5.2.1 Filters**

Filters in beamlines are primarily used to reduce the bandpass of the beam and thus the power load on the elements that interact with the beam (windows, monochromator crystals, etc.). For x-ray beamlines, a combination of high pass and low pass filters, such as a beam-deflecting mirror is very effective. These combinations are also able to suppress higher order reflections in the monochromatic beam.

The filter assembly is designed to provide a modular beamline filtering system. The assembly consists of a housing with a selection of linear filter mounts. The assembly or the linear filter mounts can be placed in every vacuum segment of the user's beamline. For ease of replacement, the filter foils are mounted on standardized filter frames. The filter frames can carry up to five different foils. The filters are linearly moved into the beam by a light load actuator. The positions of the filters must be interlocked with the beam. This protects the filter frames from being hit by the beam. The filter frames are directly cooled. In the case of radiation cooling, the surrounding vacuum chamber is protected by water-cooled radiation shielding or is directly cooled. A typical filter assembly is shown in Fig. 3.5.1.

#### **5.2.2 Beamline Windows**

Windows are used to separate beamline sections with different vacuum and pressure conditions, such as UHV, HV, and ambient pressure. For the transmission of radiation through the windows, the design criteria established for the filters is used. The vacuum tightness of the windows ( $<1 \times 10^{-10}$  torr/sec) together with the pressure difference at a transition from vacuum to atmosphere are additional complications of the window design. The main difficulty is introduced by the heat load of the ID beams, which can introduce power loads in the kW range. In these cases, windows have to be protected by filters, which absorb a large share of the heat load. Such filter-window combinations, however, severely limit the availability of the radiation spectrum below about 5-6 keV. For many CATs, it would be desirable to operate the beamline




Figure 3.5.1 APS beamline filter assembly

without a window on the ID beamlines to retain the flexibility of using the entire energy spectrum. It should be pointed out that if the CAT's interest is primarily in the hard x-ray region ( $> 10\text{keV}$ ), the use of Al windows may be appropriate.

At the APS, failure criteria and thermal and stress analysis of filters and windows have been carried out as part of the R&D program in support of construction.

The following are the design criteria for a variety of conditions:

1. A window suitable for white radiation from an APS wiggler (with  $K = 14$  and operated at  $7\text{ GeV}$ ,  $100\text{ mA}$  stored current). This can also be used for monochromatic radiation from the APS IDs.
2. A double exit window to deliver both white and/or monochromatic radiation from either an APS ID or bending magnet source.
3. A window suitable for transmitting bending magnet white radiation with a horizontal width of approximately  $110\text{ mm}$ .
4. A differential pump capable of supporting windowless configuration with a minimal aperture of  $10 \times 78\text{ mm}$  and maintaining at least two orders of magnitude difference in pressure.

In Figs. 3.5.2-5, the Title I design for all the above four configurations is provided.

Additional R&D work will be pursued to test the feasibility of pyrolytic graphite windows and diamond windows.

### 5.2.3 Beamline Slits

The slits that will be used in the beamlines will require a sophisticated design that depends on their application. For example, the white radiation slit normally has to absorb a large amount of heat from the radiation beam, while the monochromatic slits sometimes need to provide sub-micron collimation. Thus, the design of slits and the choice of the material for their construction is closely related to their application. In addition, the slits might directly impact the scientific goal of the beamline. Hence, the CATs will contribute in a major way to the slit design.

For the present, the APS has put much emphasis on the power handling issue related to slit designs. These designs will meet much of the user needs early on during beamline operation. More specific designs to cater to specific scientific experiments will be under taken by the APS as the needs become better defined.

The Title I designs for the following slits are now complete:

1. An ID white beam slit capable of positional resolution of  $2\text{ }\mu\text{m}$  and positional reproducibility of  $5\text{ }\mu\text{m}$ . This slit can provide a vertical aperture of  $0\text{-}30\text{ mm}$  and a horizontal aperture of  $0\text{-}100\text{ mm}$ . The beam intercepts the slits with a grazing incidence of about  $3^\circ$ . Water-cooled copper foam removes the heat from the slit blades. The design uses an APS standard heavy load stepping linear actuator to provide the necessary motion.
2. A BM white beam slit capable of positional resolution of  $10\text{ }\mu\text{m}$  and positional reproducibility of  $25\text{ }\mu\text{m}$ . This slit can provide a vertical aperture of  $0\text{-}30\text{ mm}$  and a horizontal aperture of  $0\text{-}150\text{ mm}$ . The beam intercepts the slits with a normal incidence.




Fig. 3.5.2 Window for wiggler white beam and wiggler/undulator monochromatic beam




Fig. 3.5.3 Monochromatic and white beam dual window




Fig. 3.5.4 Bending magnet white beam window




Fig. 3.5.5 Differential pump capable of supporting a windowless configuration

Water cooling is provided to the blades of the slits. The design uses an APS standard light load stepping linear actuator to provide the necessary motion.

3. An ID monochromatic beam slit provides a precise aperture for the monochromatic synchrotron radiation from IDs. This slit can also be used for monochromatic radiation from the bending magnet source. It provides a positional resolution of 1  $\mu\text{m}$  and a positional reproducibility of 5 - 10  $\mu\text{m}$ . The vertical aperture is 0-30 mm, and the horizontal aperture is 0-120 mm. The design uses convective air cooling to remove the heat from the slit blades.

In Figs. 3.5.6-8, the Title I designs for the above three slits are presented.

#### **5.2.4 Beam Absorbers and Beam Stops**

The white beams from IDs or bending magnet sources are stopped by a combination of photon absorbers and heavy-metal beam stops. These integral assemblies alone can completely stop the white radiation. In order to have a safe operating scheme, the absorber and the stop will be locked with a Kirk key system. The absorbers, which are made up of OFHC copper with Glid-Cop face plate, can handle a maximum power load of 5 kW. The design uses the concept that has been implemented in the beam stops designed for the ID front ends.

The monochromatic beam shutter is designed to handle monochromatic beam loads from the IDs. In this design, the heat load is conducted by a copper rod to a conventional air-cooled radiator.

In Fig. 3.5.9, the Title I design for the white and monochromatic beam stops is presented.

#### **5.2.5 Mirror Chambers**

Mirror chambers are used to provide a stable, vibration- and force-free support of beam deflecting mirrors. The chamber must allow the very precise alignment of the mirror. A resolution of the deflection angle of better than 1  $\mu\text{rad}$  has to be achieved. The vacuum conditions in the chamber ( $<1 \times 10^{-9}$  torr) shall avoid carbon contamination of the reflecting surface. In combination with high power ID beamlines, effective cooling must be supplied. The chamber has to allow bending of the mirror for variable focusing.

With the above requirements for mirror chambers, the following design criteria have been established. The mirror will be aligned by moving the whole chamber. The linear and rotation motions will be mechanically decoupled. The mirror support will be provided by a rigid central chamber frame. The resolution of the deflection angle of better than 1  $\mu\text{rad}$  is achieved through friction-free rotational motion. The chamber movement will be decoupled from the beamline by the use of formed bellows with  $\pm 25$  mm linear movement.

The Title I design of x-ray mirror chamber is shown in Fig. 3.5.10. Such a design has successfully been used on high-power beamlines at HASYLAB in Hamburg, Germany.

#### **5.2.6 Photon Beam Position Monitors and Supports**

In the front end of each of the beamlines, white radiation position monitors will be installed. These will provide both the spatial and angular position of the photon beam. Signals from these monitors will be provided to the users of the beamline. In situations where the CAT would like to obtain independent information on the white beam delivered to the first optics enclosure, an additional monitor, similar to the that in the front end, will be provided.




Fig. 3.5.6 ID white beam horizontal and vertical slits




Fig. 3.5.7 BM white beam horizontal and vertical slits




Fig. 3.5.8 ID monochromatic beam horizontal and vertical slits




Fig. 3.5.9 White and monochromatic integral shutters and stops




Fig. 3.5.10 X-ray mirror chamber for high power beamlines

The monochromatic beam position monitors are designed with a resolution of 0.1 - 0.5  $\mu\text{m}$ . The type of monitor will be provided by the users because it will have direct implications to the scientific program. The support system however has been designed by the APS and will employ supports similar to those used in the front end with a linear resolution of 0.2  $\mu\text{m}$  and angular resolution of 0.5 arcseconds.

The conceptual design for a support for the monochromatic beam position monitor has been completed and is shown in Fig. 3.5.11.

### **5.2.7. Stepping Motor Drivers and Controllers**

Standardizing stepping motor drivers and controllers for the user applications is extremely desirable. However, because of the user proximity to such components, it is expected that some of the users will design their own systems. Here, general guidance is provided that we hope will lead to standard designs compatible to various user applications.

The capability of the standard stepping motor drivers and the controllers should be to support multiple motors (up to 100), open- and/or closed-loop control, acceleration and deceleration control, and power fail-safe control with memory backup. It would also be essential to standardize connectors and cables. The detailed specifications will be provided as activity with the CATs matures during FY 1993-94.

### **5.2.8 Actuators**

The actuators play a major role in the design of a number of beamline components. Actuators may be needed for the white and monochromatic slits, beam stops, and safety shutters. The design work has been completed on heavy load and light load actuators coupled to a stepping motor drive or to a pneumatic drive.

In Figs. 3.5.12-15, the design for four of these actuators is given.

### **5.2.9 First Optics Enclosures and Experimental Stations**

The first optics enclosures and the experimental stations (hutches) are designed using a modular concept to provide flexibility to the CATs. The enclosures are made of lead and steel. The lead provides the necessary radiation shielding for synchrotron radiation and bremsstrahlung. The thickness of lead shielding is now being carefully determined using detailed calculations and the experience at other synchrotron facilities.

Here, only preliminary concepts are provided. These concepts will be closely examined during FY 1993. In Figs. 3.5.16-17, Title I layouts of a first optics enclosure and an experimental station are provided.

### **5.2.10 Supports and Kinematic Mounts**

There are many requirements for support stages and kinematic mounts in every beamline. Hence, the supports and kinematic mounts are designed with various scientific applications in mind. Some of the designs provide coarse resolution, while others provide precision movements. Some of them can accept large loads, while some are for small loads. Prototypes of some of the supports and kinematic mounts have been built to test their capabilities under extreme load conditions.







Fig. 3.5.11 Monochromatic beam position monitor support

Fig. 3.5.12 APS heavy load stepping linear actuator






APS HEAVY LOAD STEPPING LINEAR ACTUATOR  
 SLAH-30-8  
 SIDE VIEW  
 1/20/93  
 C. BRITE



APS HEAVY LOAD STEPPING LINEAR ACTUATOR  
 SLAH-30-8  
 ELEVATION  
 1/20/93  
 C. BRITE






APS LIGHT LOAD STEPPING LINEAR ACTUATOR  
SLAL-75-8  
1/26/93  
C. BRITE

Fig. 3.5.14 APS light load stepping linear actuator

# A3-81, 31mm STROKE



# A3-83, 70 mm STROKE




Fig. 3.5.15 APS light load pneumatic linear actuator






Fig. 3.5.16 First optics enclosure




Fig. 3.5.17 Experimental station (hutch)

Only two of the concepts are presented in Figs. 3.5.18-19. These are a precision table with a 1000-Kg load capacity, a 10- $\mu\text{m}$  motional resolution, and 50- $\mu\text{m}$  repeatability. This table can be operated using stepping motors or manually depending on the application. The standard table has the same load capacity as the precision table, but provides only 125- $\mu\text{m}$  resolution and a 400- $\mu\text{m}$  repeatability. Indeed, the standard design can be built at a considerably lower price.

- SPECIFICATIONS:
1. LOAD CAPACITY: 2200 LBS [1000 kg]
  2. TRAVEL RANGE: +/- .25 [6.35]
  3. DEGREES OF FREEDOM: 5
  4. REPEATABILITY: 50  $\mu$ m
  5. RESOLUTION: 10  $\mu$ m
  6. HORIZONTAL AND VERTICAL ADJUSTMENT: STEPPER MOTOR




Fig. 3.5 18 Support base with precision kinematic mount stages



## 6. REFERENCES

- <sup>1</sup> 7-GeV Advanced Photon Source Conceptual Design Report, ANL-87-15 (1987).
- <sup>2</sup> G. K. Shenoy, P. J. Viccaro, and D. M. Mills, Characteristics of the 7-GeV Advanced Photon Source: A Guide for Users, ANL-88-9 (1988).
- <sup>3</sup> S. L. Xu, B. Lai, and P. J. Viccaro, APS Undulator and Wiggler Sources: Monte-Carlo Simulation, ANL/APS/TB-1 (1992).
- <sup>4</sup> G. K. Shenoy, unpublished.
- <sup>5</sup> H. Kitamura and S. Yamamoto, *Rev. Sci. Instrum.*, to be published.

## CHAPTER IV COST AND SCHEDULE

### 1. INTRODUCTION TO COST AND SCHEDULE

All costs for the Beamline Initiative are developed from the Work Breakdown Structure (WBS) and are expressed in FY 1993 dollars. The WBS encompasses all elements of the construction phase from the design to the end of construction. The experimental facilities technical components were designed by the staff of the APS Experimental Facilities Division (XFD), who also estimated their costs. A complete planned WBS is shown in Table 4.1.1. The WBS shows the Beamline Initiative at level 1. Level 2 shows the functional responsibility that includes the experimental facilities. Also included at this level are project management overheads and contingency. The technical components of the experimental facilities are defined at WBS level 3 (e.g., 4.4.1). All costs of materials, construction, and inspection (I) are estimated at an appropriate WBS level and rolled up to develop the final costs at WBS level 2. The costs of Engineering and Design (ED) are not included here because the design and engineering work is already completed as part of the current construction phase.

The cost estimates include all costs for PACE construction to be incurred after the Beamline Initiative approval. The scope of this initiative includes construction of equipment behind the shield wall for four additional sectors and the standard components of the beamlines.

It should be pointed out that the standard components of beamlines have been described as examples in Chapter III. In selecting the final standard components to be provided to various CAT beamlines for the Beamline Initiative, these examples as well as other ideas from the user community will be used. Typical costs for each of these standard components have been estimated. The list and the number of these components that will be built as part of this initiative will be developed after the Title I designs of the CAT beamlines are reviewed by the APS.

The costs for R&D in support of construction, operations, and for commissioning the experimental facilities are also included in this cost estimate.

Table 4.1.1

APS Beamline Initiative Work Breakdown Structure

WBS Code	Element Description
X.4.0	APS Beamline Initiative
X.4.1	Project Management (Beamline Initiative)
X.4.4	Experimental Facilities
X.4.4.1	Experimental Facilities Technical Components
X.4.4.1.1	Insertion Devices (4)
X.4.4.1.2	Beamline Front Ends (8)
X.4.4.1.5	Standard Components of Beamlines

## 2. COST ESTIMATES

The direct cost elements such as labor, materials and services, direct material, and subcontracts are broken down into various craft codes. These have been listed in Table 4.2.1. The rates used for the various crafts are given in Table 4.2.2 as hourly rates in FY 1993 dollars.

The work in each element of the WBS is divided into eight activities: design, procurement, fabrication, assembly, testing, installing, checkout, and Level of Effort (LOE). The last activity, namely LOE, is the administrative effort involved in performing the work and does not have a true final product.

All the overhead and paid-absence costs for the construction activity are included separately along with the rest of the APS construction project. However, in deriving the man-year numbers, the paid-absence fraction is included.

A cost breakdown by WBS code for the Beamline Initiative is shown in Table 4.2.3 in FY 1993 dollars. The cost estimates for the conventional facilities include two elements: 1) construction costs. and (2) the inspection cost.

All cost estimates for the experimental facilities technical components include three basic elements: 1) costs of hardware deliverable (materials), 2) construction costs, and 3) inspection costs. These elements are given in detail in Section 4.

Table 4.2.1

Cost Account Planning - Direct Cost Elements

Labor Classifications - APS

- 101 - Staff (Physicist, Engineer, Computer Designer, Project Management)
- 111 - Salaried (Chief Technician, Ex. Secretary, Admin. Asst.)
- 121 - Hourly (Technician T1/T2, Drafter, Sec./Clerk, Non-Union)
- 131 - Hourly (Union Standard Rate)
- 141 - Temporary (Post. Doc.)
- 161 - Temporary (Hourly)
- 505 - Special Term Appointees (STA)

M&S - Material & Services

- 400 - Travel & Living
- 430 - Educational Reimbursements
- 416 - Seminars, Conferences
- 422 - Scientific Equipment Maintenance
- 427 - Computer Software
- 405 - Equipment Rental
- 499 - Miscellaneous ODC

ANL Service Centers

- 521 - ANL Central Shops
- 571 - ANL Electronics Division
- 561 - ANL Graphics Arts Services
- 550 - ANL Computer Services Division
- 520 - ANL Engineering Division
- 590 - ANL - All Other Support

Direct Material

- 390 - Material purchased through APS Procurement Cell
- 390 - Freight and transportation related costs for materials
- 390 - Stock issues from ANL stores
- 390 - Purchase orders initiated by ANL shops

Subcontracts

- 402 - Personal service subcontracts w/individuals
- 403 - Personal service subcontracts - all others
- 410 - Outside shopwork and installation costs

Table 4.2.2  
 Craft Codes and Hourly Rates (FY 93\$)

---

<u>Engineering, Design and Inspection (ED&amp;I):*</u>		
101-PH	-Physicist	\$34.59
101-EN	-Engineer Mechanical and Electrical	\$34.59
101-SW	-Computer Designer (Software)	\$34.59
101-DC	-Designer/Design Coordinator	\$34.59
121-DR	-Drafter	\$19.50
141-	-Postdoc	\$23.95
 <u>Construction:</u>		
<u>Assembly and Test:**</u>		
121-T1	-Technician, relatively unskilled	\$19.50
121-T2	-Technician, experienced/skilled	\$19.50
 <u>Fabrication/Manufacturing:</u>		
521-	-ANL Fabrication/Manufacturing Support	\$54.40
 <u>Installation Subcontracts ("Davis-Bacon"):**</u>		
410-IP	-Plumber, Steam Fitter Sheet Metal	\$50.00
410-IE	-Electrician	\$50.00
410-IC	-Carpenter	\$50.00
410-IT	-Technician	\$50.00
 <u>Level of Effort (LOE):</u>		
101-MN	-Project Manager	\$34.59
121-SS	-Secretarial Support	\$19.50
101-EN	-Project Engineer	\$34.59

---

\* Includes effective hourly base pay and benefits, but does not include lab overheads.

\*\* Includes hourly base pay, benefits, and overheads, and profit for "outside" vendor or contractor.

Table 4.2.3

**APS BEAMLINe INITIATIVE COST BREAKDOWN BY WBS CODE**

<b>WBS Code</b>	<b>Description</b>	<b>Cost in FY 93 M\$</b>
4.0	APS Instrumentation Initiative	
4.1	Project Management (2% of Construction Cost)	0.75
4.4	Experimental Facilities	37.75
4.4.1	Experimental Facilities Technical Components	37.75
4.1.1.1	Insertion Devices	4.47
4.4.1.2	Beamline Front Ends	6.22
4.4.1.5	Standard Components of Beamlines	27.06
	Contingency (10.5% of Construction Cost)	3.96
	Overheads (5%)	2.12
	<b>Total Estimated Cost (TEC)</b>	<b>44.58</b>
	R&D in Support of Construction	2.76
	Other Project Costs	5.15
	Capital Equipment	11.13
	Inventories	0.90
	<b>Total Project Cost (TPC)</b>	<b>64.52</b>

### **3. TIME SCHEDULE**

The experimental facilities technical components will be using existing facilities from the current phase. Therefore, there will be no conflict of schedule with the current phase. The design, construction, and installation time schedule is based on experience of personnel at APS and other laboratories as well as vendor quotations. The installation of the technical components behind the shield wall is scheduled to coincide with the shutdown and maintenance schedule during operations.

Figure 4.3.1 shows the time schedule estimated for both the conventional and the experimental facilities.

### **4. COST SCHEDULE**

Using the detailed WBS cost estimate in Table 4.2.3, which contains the cost of materials and labor of various crafts, and the time schedule shown in Figure 4.3.1 developed for completion of these activities, a cost schedule profile has been generated and is shown in Table 4.4.1 and Figure 4.4.1. In addition to the cost elements previously mentioned for both the conventional and experimental facilities, included in this profile are: 1) laboratory overheads estimated at 5% of construction costs for indirect expenses (such as procurement, accounting, human resources, etc.) and maintenance of facilities, 2) contingency costs estimated at 10.5% of construction cost, because the cost of the specialized insertion devices, front ends, and the standard components of the beamlines may vary.

Applying the escalation rates given in Table 4.4.2, the escalated cost schedule profile shown in Table 4.4.3 was generated and is graphically presented in Figure 4.4.2.

The budget BA/BO profile (Budget Authorization/Budget Obligated) for the construction project is broken down by fiscal year and is shown in Table 4.4.4 and Figure 4.4.3.

**APS BEAMLINE INITIATIVE CONSTRUCTION TIME SCHEDULE**

WBS ELEMENT	FY 1996	FY 1997	FY 1998	FY 1999
4.4.1.1 Insertion Devices	[Hatched]	[Hatched]	[Hatched]	[Hatched]
4.4.1.2 Beamline Front Ends	[Hatched]	[Hatched]	[Hatched]	[Hatched]
4.4.1.5 Beamline Standard Components	[Hatched]	[Hatched]	[Hatched]	[Hatched]

Figure 4.3.1


Table 4.4.1

**APS BEAMLINE INITIATIVE COST SCHEDULE  
(FY93 M \$)**

WBS NUMBER	ITEM	1996	1997	1998	1999	Total
4.1	Project Management(2% )	0.05	0.31	0.22	0.17	0.75
4.4	Experimental Facilities	2.40	15.56	11.15	8.64	37.75
	ED & I (7.9%)	0.18	1.14	0.82	0.63	2.76
	Construction Effort	0.32	2.19	1.68	1.36	5.55
	Materials	1.90	12.23	8.65	6.65	29.43
	<b>Subtotal</b>	<b>2.45</b>	<b>15.87</b>	<b>11.37</b>	<b>8.81</b>	<b>38.50</b>
	Overheads (5%)	0.13	0.88	0.63	0.49	2.13
	Contingency (10.5%)	0.25	1.63	1.17	0.91	3.96
	<b>Total TEC</b>	<b>2.83</b>	<b>18.38</b>	<b>13.17</b>	<b>10.21</b>	<b>44.59</b>
	R&D in Support of Construction	0.95	1.37	0.44	0.00	2.76
	Other Project Costs	0.00	0.00	1.76	3.39	5.15
	Capital Equipment	1.61	0.91	3.52	5.09	11.13
	Inventories	0.00	0.46	0.44	0.00	0.90
	<b>Total TPC</b>	<b>5.39</b>	<b>21.12</b>	<b>19.33</b>	<b>18.69</b>	<b>64.52</b>

Figure 4.4.1

### APS BEAMLINE INITIATIVE COST SCHEDULE



**Table 4.4.2**

**Escalated Rates**

<b>Fiscal Year</b>	<b>Inflation (%)</b>	<b>Escalation Factor</b>
1993	-	1.000
1996	11.7	1.117
1997	3.8	1.160
1998	3.5	1.200
1999	3.8	1.245

Table 4.4.3

**APS BEAMLINE INITIATIVE COST SCHEDULE**  
**(Escalated M \$)**

WBS NUMBER	ITEM	1996	1997	1998	1999	Total
4.1	Project Management (2% )	0.05	0.36	0.27	0.22	0.90
4.4	Experimental Facilities	2.68	18.04	13.39	10.77	44.87
	ED & I (7.9%)	0.20	1.32	0.98	0.79	3.29
	Construction Effort	0.36	2.54	2.02	1.69	6.61
	Materials	2.12	14.18	10.39	8.28	34.98
	<b>Subtotal</b>	<b>2.73</b>	<b>18.40</b>	<b>13.66</b>	<b>10.98</b>	<b>45.77</b>
	Overhead (5%)	0.15	1.01	0.75	0.61	2.52
	Contingency (10.5%)	0.28	1.89	1.41	1.13	4.71
	<b>Total TEC</b>	<b>3.16</b>	<b>21.30</b>	<b>15.82</b>	<b>12.72</b>	<b>53.00</b>
	R&D in Support of Construction	1.06	1.59	0.53	0.00	3.18
	Other Project Costs	0.00	0.00	2.11	4.22	6.33
	Capital Equipment	1.80	1.06	4.23	6.34	13.43
	Inventories	0.00	0.53	0.53	0.00	1.06
	<b>Total TPC</b>	<b>6.02</b>	<b>24.48</b>	<b>23.22</b>	<b>23.28</b>	<b>77.00</b>

Figure 4.4.2

# APS BEAMLINE INITIATIVE TEC AND TPC IN FY 93 DOLLARS





Table 4.4.4

**BA/BO Profile (Escalated M\$)**

	1996	1997	1998	1999	TOTAL
Escalated BA	3.20	21.30	15.80	12.70	53.00
Escalated BO	3.00	13.50	19.20	17.30	53.00

Figure 4.4.3

### APS BEAMLINE INITIATIVE BUDGET AND COST PROFILE





**APPENDIX 1**

**COLLABORATIVE ACCESS TEAM SUMMARIES**



# BESSRC-CAT

## Basic Energy Sciences Synchrotron Radiation Center CAT

CAT Director and Affiliation	CAT Deputy Director and Affiliation	Institutional Affiliations of Participating Investigators
Pedro A. Montano Argonne Natl. Lab. telephone (708)252-6239 fax (708)252-7777	Gordon S. Knapp Argonne Natl. Lab. telephone (708)252-5488 fax (708)252-7777	Argonne Natl. Lab., ORNL/Univ. of Tennessee

*Discipline:* Basic Energy Sciences

*Sector(s):* 2

*Focus:* Particular emphasis will be placed in the areas of materials science, chemical science, and atomic physics. Among the specific studies planned are time-resolved studies of photoexcited states in photosynthetic materials, real-time investigations of chemical reactions, and time-dependent structural studies of phase transformations in solid compounds. Also planned are structural studies of actinides, studies of ultra-small crystals, trace element analysis, and *in situ* studies of microclusters. Surfaces and interfaces will be investigated, and selective elemental depth profiling techniques will be developed. Structural and magnetic properties of alloys and thin films will be investigated by using circularly polarized x-rays produced by an elliptical multipole wiggler insertion device. Four beamlines with 11 experimental stations will be developed for maximum scientific and cross-disciplinary flexibility.

*Other Key Individuals:*

Yoshiro Azuma	Physics Division	Argonne Natl. Lab.
Michael Bedzyk	Materials Science Division	Argonne Natl. Lab.
Mark A. Beno	Materials Science Division	Argonne Natl. Lab.
Ronald Chiarello	Materials Science Division	Argonne Natl. Lab.
Paul L. Cowan	Physics Division	Argonne Natl. Lab.
Guy Jennings	Materials Science Division	Argonne Natl. Lab.
James R. Norris	Chemistry Division	Argonne Natl. Lab.
Mohan Ramanathan	Materials Science Division	Argonne Natl. Lab.
Stephen J. Riley	Chemistry Division	Argonne Natl. Lab.
Ivan A. Sellin		ORNL/Univ. of Tenn.
Lynda C. Soderholm	Chemistry Division	Argonne Natl. Lab.
Randall Winans	Chemistry Division	Argonne Natl. Lab.
Hoydoo You	Materials Science Division	Argonne Natl. Lab.

# Bio-CAT Biophysics CAT

## CAT Director and Affiliation

Grant Bunker  
Illinois Inst. of Technology  
telephone (312)567-3385  
fax (312)567-3396

## Institutional Affiliations of Participating Investigators

Boston Univ., Brandeis Univ., Brookhaven Natl. Lab., Bulgarian Academy of Science, Carnegie-Mellon Univ., Childrens Hospital Medical Center, Cornell, Drexel, Georgetown Univ., Harvard, Illinois Inst. of Technol., Johns Hopkins, GFF Ctr., KFG Technology Center, Kings College, Lawrence Berkeley Lab., Marquette, N. Carolina State Univ., Northwestern University, NIH, Ohio State, Oregon Grad. Inst. of Science & Tech., Princeton, Roswell Park, Stanford Univ., Univ. Connecticut, Univ. of Georgia, Univ. of Illinois, Univ. of Michigan, Univ. of Minnesota, Univ. of Missouri, Univ. of Pennsylvania, Univ. of Rochester, Univ. of Wisconsin, VA Med. Ctr., Vanderbilt, Yale Univ.

*Discipline:* Biophysics

*Sector(s):* 1

*Focus:* The major emphasis of this group will be the study of the structure and dynamics of biological and related systems at the molecular level, with a focus on partially ordered samples such as membranes, fibers, and solutions. The primary research techniques will be resonant (anomalous) and nonresonant x-ray diffraction, and x-ray absorption fine structure (XAFS) spectroscopy, with emphasis on time-resolved studies, polarized XAFS, hybrid diffraction/spectroscopic techniques, and novel techniques that exploit the unique properties of the APS.

### *Other Key Individuals:*

J. Kent Blasie	Univ. of Pennsylvania
Allen Blaurock	Kraft General Foods
Martin Caffrey	Ohio State Univ.
Malcolm Capel	Brookhaven Natl. Lab.
Donald L. Caspar	Brandeis Univ.
Britton Chance	Univ. of Pennsylvania
Sol Gruner	Princeton Univ.
Keith Hodgson	SSRL

Richard Korszun	Univ. of Wisc.-Parkside
Lee Makowski	Boston Univ.
James Penner-Hahn	Univ. of Michigan
Gerold Rosenbaum	Argonne Natl. Lab.
Dale Sayers	N. Carolina State Univ.
Elizabeth Theil	N. Carolina State Univ.
Edwin Westbrook	Argonne Natl. Lab.

# CARS-CAT

## Consortium for Advanced Radiation Sources CAT

### CAT Director and Affiliation

J. Keith Moffat  
The Univ. of Chicago  
telephone (312)702-2116 or  
(312)702-9950  
fax (312)702-1896 or  
(312)702-5454

### Institutional Affiliations of Participating Investigators

Air Products & Chemicals, Inc., Argonne National Lab., BioSymb Tech., Brandeis Univ., Bristol Univ., Brookhaven Natl. Lab., California Inst. of Tech., Carnegie Institute of Washington, Carnegie-Mellon Univ., Columbia Univ., Cornell University, Environ. Protect. Agency, Georgia State Univ., Harvard Med. School, Harvard University, IBM Almaden Res. Cent., Iowa State Univ., Johns Hopkins Univ., Kansas State Univ., Lunar and Planetary Inst., Manhattan Coll., Michigan State Univ., MIT, Mobil R&D, No. Dakota State Univ., Northeastern Univ., Northern Illinois Univ., Ohio State Univ., Penn. State Univ., Purdue Univ., Research Inst. of Scripps Clinic, Rutgers Univ., Southern Illinois Univ., Stanford Univ., St. Francis Xavier Univ., SUNY, Texas A&M Univ., The Univ. of Chicago, The Wistar Institute, UCLA, Univ. of Alabama, Univ. of Alberta, Univ. of California, Univ. of Chicago Med. Cent., Univ. of Cincinnati, Univ. of Delaware, Univ. of Edinburgh, Univ. of Georgia, Univ. of Hawaii, Univ. of Illinois, Univ. of Mass., Univ. of New Mexico, Univ. of Oxford, Univ. of Puerto Rico, Univ. of Texas, Univ. of Toronto, Univ. of Virginia, Univ. of Wisconsin, USDA-ARS, Virginia PI & SU, Washington State Univ., Weizmann Inst. of Science

*Discipline:* Structural Biology, Geosciences, Chemical Sciences, Material Science, Soil/Environmental Sciences

*Sector(s):* 2

*Focus:* This multidisciplinary group, which contains more than 140 scientists from four national users groups (BioCARS, ChemCARS, GeoCARS, Soil/EnviroCARS), and three Illinois universities, will enable scientists from several disciplines to interact and receive maximum exposure to new approaches and techniques. In the area of structural biology, the emphasis will be on elucidation of molecular structure, particularly from crystals with very large unit cells, such as viruses, and from microcrystals and crystals suitable for multiple wavelength anomalous dispersion phasing. In addition, time-resolved studies of biological processes in crystals, fibers, membranes, and solutions will be conducted. Earth, planetary, and soil/environmental sciences research will include surface scattering, microcrystallography, and time-resolved work, as well as high-pressure diffraction, spectroscopy, microprobe analyses, and powder diffraction. These techniques should make possible major advances in understanding such diverse processes as earthquake development, and nitrogen fixation in roots. Chemical sciences studies will involve single-crystal diffraction, spectroscopy, surface scattering, and small-angle scattering for external surface studies; chemical crystallography; x-ray absorption spectroscopy; study of metal clusters, metallic glasses and transmetalation chemistry; study of microporous and layered materials; and polymer studies.

### *Other Key Individuals:*

#### Members of CARS Board of Governors:

P.M. Bertsch	Univ. of Georgia	V. Molfese	So. Illinois Univ.
G.E. Borwn Jr.	Stanford Univ.	W.H. Orme-Johnson	MIT
L.F. Dohl	Univ. of Wisconsin	C.T. Prewitt	Carnegie Inst. of Wash.
J.E. Johnson	Purdue Univ.	S.A. Rice	Univ. of Chicago
C.W. Kimball (Chairman)	No. Illinois Univ.	D.G. Schulze	Purdue Univ.
E. Lattman	Johns Hopkins Univ.	J.H. Yopp	So. Illinois Univ.
M.W. Makinen	Univ. of Chicago	J.H. Zar	No. Illinois Univ.

#### Members of CARS Coordinating Committee (Univ. of Chicago)

J.K. Moffat (Chairman)	M.L. Rivers	F. Stafford	P.J. Viccaro
S.A. Rice	W. Schildkamp	S. Sutton	J. Talsma
J.V. Smith			

# CMC-CAT

## Complex Materials CAT

CAT Director and Affiliation	CAT Deputy Director and Affiliation	Institutional Affiliations of Participating Investigators
Sunil K. Sinha Exxon Res. & Engineering telephone (908)730-2875 fax (908)730-3031	Richard C. Hewitt Exxon Res. & Engineering telephone (516)282-4828 516/282-5239	BARC India, Brookhaven Natl. Lab., Exxon Res. & Engineering, Princeton Univ., Univ. of California-Santa Barbara, Univ. of Pennsylvania, Univ. of Tennessee/Oak Ridge Natl. Lab.

*Discipline:* Structural Characterization of Complex Materials

*Sector(s):* 1

*Focus:* This group will focus on the structural characterization of complex materials, including complex fluids and self-assembling systems, surfaces and interfaces, and heterogeneous materials. Experimental techniques to be used include the following: time-dependent diffraction and scattering studies, high-resolution small-angle scattering and crystallography, surface scattering, photon-correlation spectroscopy, and several types of imaging techniques.

*Other Key Individuals:*

J. Kent Blasie	Univ. of Pennsylvania	B. M. Ocko	Brookhaven Natl. Lab.
T. Egami	Univ of Pennsylvania	E. Ward Plummer	Univ. of Tenn./ORNL
Peter M. Eisenberger	Princeton University	R. A. Register	Princeton Univ.
J. Fischer	Univ. of Pennsylvania	C. R. Safinya	Univ. of Calif/Santa Barbara
L. D. Gibbs	Brookhaven Natl. Lab.	M. Sansone	Exxon Res. & Engineering
Sol M. Gruner	Princeton Univ.	M. X. Sanyal	BARC India
P. Heiney	Univ. of Pennsylvania	E. B. Sirota	Exxon Res. & Engineering
H. E. King, Jr.	Exxon Res. & Engineering	G. H. Via	Exxon Res. & Engineering
K. S. Liang	Exxon Res. & Engineering		

# DND-CAT

## E.I. Du Pont de Nemours & Co. - Northwestern University - The Dow Chemical Co. CAT

CAT Chairman and Affiliation	CAT Director and Affiliation	Institutional Affiliations of Participating Investigators
Jerome B. Cohen Northwestern Univ. telephone (708)491-5220 fax (708)491-8539	Panayotis (Joe) Georgopoulos Synchrotron Research Center telephone (708)864-0077 fax (708)864-0196	The Dow Chemical Co., E.I. Du Pont de Nemours & Co., Northwestern Univ.

*Discipline:* Surface and Interface Science, Polymer Science and Technology, Materials Science

*Sector(s):* 1

*Focus:* Although many fields of materials science and engineering will be represented by this research group, the major effort will be directed to two areas: the study of two-dimensional and quasi-two-dimensional atomic structures (surfaces, interfaces, and thin films) and polymer science and technology. In the first area, specific areas of interest include the study of solid-liquid electrolyte interfaces, oxide surfaces, intercrystalline interfaces, thin-film growth *in situ*, and polymer film surfaces. In the polymer science area, this group will study polymer deformation, crystallization and melting of polymers, and polymer deformation and fracture. In addition, some work will be conducted in the area of atomic structure of bulk materials.

*Other Key Individuals:*

Simon Bare	The Dow Chemical Co.	James A. Ibers	Northwestern Univ.
Scott Barnett	Northwestern Univ.	Hamlin Jennings	Northwestern Univ.
Randolph Barton	E.I. Du Pont de Nemours & Co.	Robert C. Johnson	E.I. Du Pont de Nemours & Co.
Michael J. Bedzyk	Northwestern Univ.	Glover A. Jones	E.I. Du Pont de Nemours & Co.
Robert Bubeck	The Dow Chemical Co.	Denis Keane	Northwestern Univ.
J.C. Calabrese	E.I. Du Pont de Nemours & Co.	John B. Ketterson	Northwestern Univ.
Stephen H. Carr	Northwestern Univ.	Warren Knox	The Dow Chemical Co.
Robert P. H. Chang	Northwestern Univ.	Harold Kung	Northwestern Univ.
Yip-Wah Chung	Northwestern Univ.	Brian Landes	The Dow Chemical Co.
Don Coulman	E.I. Du Pont de Nemours & Co.	Joe Maj	The Dow Chemical Co.
George Coulston	E.I. Du Pont de Nemours & Co.	William Marshall	E.I. Du Pont de Nemours & Co.
Michael Crawford	E.I. Du Pont de Nemours & Co.	Chad Mirkin	Northwestern Univ.
Buckley Crist, Jr.	Northwestern Univ.	Gary Mitchell	The Dow Chemical Co.
Cyrus Crowder	The Dow Chemical Co.	Becky Moore	The Dow Chemical Co.
Isaac M. Daniel	Northwestern Univ.	Brian Moran	Northwestern Univ.
Benjamin DeKoven	The Dow Chemical Co.	Bob Newman	The Dow Chemical Co.
Ashok Dhere	E.I. Du Pont de Nemours & Co.	Ken Poeppelmeier	Northwestern Univ.
Yuri Dolin	Northwestern Univ.	John Quintana	Northwestern Univ.
Larry Effler	The Dow Chemical Co.	Michael Radler	The Dow Chemical Co.
Donald E. Ellis	Northwestern Univ.	Ed Rightor	The Dow Chemical Co.
Katherine T. Faber	Northwestern Univ.	Phil Rudolph	The Dow Chemical Co.
Lawrence Firment	E.I. Du Pont de Nemours & Co.	David N. Seidman	Northwestern Univ.
Catharine Foris	E.I. Du Pont de Nemours & Co.	Duward F. Shriver	Northwestern Univ.
K.H. Gardner	E.I. Du Pont de Nemours & Co.	Carla Shute	Northwestern Univ.
Ralph Guerra	The Dow Chemical Co.	Charlie C. Torardi	E.I. Du Pont de Nemours & Co.
L. Guggenberger	E.I. Du Pont de Nemours & Co.	Julia Weertman	Northwestern Univ.
Richard L. Harlow	E.I. Du Pont de Nemours & Co.	Frank Wilson	E.I. Du Pont de Nemours & Co.
Mike Heany	The Dow Chemical Co.	Richard Wolcott	The Dow Chemical Co.
Paul Himes	The Dow Chemical Co.	Charlie Wood	The Dow Chemical Co.
Benjamin Hsiao	E.I. Du Pont de Nemours & Co.	Dan Q. Wu	E.I. Du Pont de Nemours & Co.

# IMCA-CAT

## Industrial Macromolecular Crystallography Association CAT

CAT Chairman and Affiliation	CAT Director and Affiliation	Institutional Affiliations of Participating Investigators
Keith Watenpaugh The Upjohn Co. telephone (616)385-7755 fax (616)385-7522	Timothy Morrison Ill. Institute of Tech. telephone (312)567-3381 fax (312)567-3396	Abbott Labs, Bristol-Myers Squibb, Merck Pharmaceutical Co., Glaxo Inc., Eli Lilly and Company, Ill. Institute of Tech., Merck & Co. Inc., Miles Inc., Monsanto Company, Parke-Davis, The Procter & Gamble Distributing Co., SmithKline Beecham Pharmaceuticals, Sterling Winthrop Inc., The Upjohn Co.

*Discipline:* Structural Biology/Macromolecular Crystallography

*Sector(s):* 1

*Focus:* This group seeks to determine the structures of biological macromolecules in order to aid in the design of biologically active compounds for medicine and agriculture, understand the mechanism of action of biological macromolecules, guide protein engineering to develop molecules with improved properties, assist in product development, and meet regulatory requirements.

*Key Features:* Both fundamental and proprietary work will be performed. It should be noted that the research groups within IMCA will, in general, have a *competitive*, rather than a *collaborative*, scientific relation.

*Other Key Individuals:*

C. Abad-Zapatero	Abbott Labs	William C. Stallings	Monsanto Co.
John S. Sack	Bristol-Myers Squibb	Joel D. Oliver	The Procter & Gamble Dist.
Karl D. Hardman	DuPont Merck Pharm. Co.	Sherin S. Abel-Meguid	SmithKline Beecham Phar.
Steven R. Jordan	Glaxo Inc.	F. Raymond Salemme	Sterling Winthrop, Inc.
James P. Springer	Merck & Co., Inc.	Keith D. Watenpaugh	The Upjohn Co.
Arthur H. Robbins	Miles Inc.		

# IMM-CAT IBM-MIT-McGill CAT

CAT Director and Affiliation	CAT Deputy Director and Affiliation	Institutional Affiliations of Participating Investigators
G. Brian Stephenson IBM Research Div. telephone (914)945-3008 fax (914)945-2141	Simon G. J. Mochrie MIT telephone (617)253-6588 fax (617)258-6883	IBM Research Div., MIT, McGill Univ., Queens Univ.

*Discipline:* Dynamic Phenomena in Materials Science and Physics

*Sector(s):* 1

*Focus:* The scientific program of IMM-CAT will focus on dynamic phenomena in materials science and condensed matter physics. Elements of our program fall into four areas: time-resolved scattering studies of bulk phase transition kinetics; scattering studies of surface structure, kinetics, and growth; scattering and spectroscopy studies of the atomic structure of buried interfaces; and intensity fluctuation spectroscopy studies using coherent x-rays. There is much in common between these areas, both in the techniques used and the systems studied. For example, measurements of kinetics will be extended from bulk phase transitions to surface phase transitions. Growth will be studied both at surfaces and at buried interfaces. X-ray diffraction techniques developed for surfaces will be applied to buried interfaces. The development of x-ray intensity fluctuation spectroscopy will allow the study of dynamics not only in non-equilibrium systems, but also in equilibrium systems, and so will provide a new probe to study all aspects of kinetics.

*Key Features:* The ID beam line will be optimized for scattering experiments and will incorporate undulator A, with flexible options for focusing and energy resolution. The BM beam line will be optimized for resonant scattering and spectroscopy.

*Other Key Individuals:*

Robert J. Birgeneau	MIT	J. David Litster	MIT
Joseph G. Gordon	IBM Research Div.	Owen Melroy	IBM Research Div.
Thomas J. Greytak	MIT	Marsha A. Singh	Queen's University
Glenn Held	IBM Research Div.	Mark Sutton	McGill University
Jean L. Jordan-Sweet	IBM Research Div.	Michael F. Toney	IBM Research Div.

# MHATT-CAT

## Center for Real-Time X-Ray Studies CAT

CAT Director and Affiliation	CAT Deputy Director and Affiliation	Institutional Affiliations of Participating Investigators
Walter Lowe Howard University telephone (202)806-4351 fax (202)806-4353	Roy Clarke University of Michigan telephone (313)764-4466 fax (313)764-2193	AT&T Bell Labs., Howard Univ., Univ. of Michigan
	Ron Pindak AT&T Bell Laboratories telephone (908)582-2719 fax (908)582-4702	

*Discipline:* Physics, Real-time Structural Studies of Materials, Chemical Sciences

*Sector(s):* 1

*Focus:* The emphasis of this group will be time-resolved studies of materials under real dynamic conditions. The microscopic analysis of physical and chemical processing, behavior under stress and structural relaxation, and the kinetic mechanisms of growth will be addressed. The beamlines to be developed will allow new kinds of coherent spectroscopic measurements of solids and complex fluids.

*Other Key Individuals:*

Gabriel Aeppli	AT&T Bell Labs	Robert M. Fleming	AT&T Bell Labs
James Allen	University of Michigan	John L. Gland	University of Michigan
Meigan Aronson	University of Michigan	A. Refik Kortan	AT&T Bell Labs
Michael Bretz	University of Michigan	Robert MacHarrie, Jr.	AT&T Bell Labs
Steve Dierker	University of Michigan	Matthew A. Marcus	AT&T Bell Labs
Kenneth Evans-Lutterodt	AT&T Bell Labs	James Penner-Hahn	University of Michigan
Robert M. Fleming	AT&T Bell Labs		

# MICRO-CAT

## A Micro-Investigation of Composition Research Organization CAT

---

**CAT Director  
and Affiliation**

Gene E. Ice  
Oak Ridge Natl. Lab.  
telephone (615)574-2744  
fax (615)574-7659

**Institutional Affiliations of Participating  
Investigators**

Lawrence Berkeley Lab., Lawrence Livermore Natl. Lab., Oak Ridge Natl. Lab., Univ. of Illinois

*Discipline:* Microprobe Analysis of Material Structure, Biological, & Environ. Samples

*Sector(s):* 1

*Focus:* This group proposes to develop and operate a microprobe facility with wide-ranging applications in the fields of materials science, chemistry, geochemistry, environmental science, and medicine. Materials science studies will include the measurement of impurity effects and strains in crack growth and fracture; ductility of grain boundaries; the study of creep, ceramics, and reinforced composites; diffusion studies; the study of integrated circuits and microchips; and radiation effects. Environmental and biological studies include such things as measurement of trace element distribution in tree rings, fish scales, clam shells, and other time-dependent growth tissues where contamination levels can be related to chronology of exposure, and the measurement of contamination transport by small particles.

*Key Features:* Ultra low minimum detectable limit with small probe dimensions. Microdiffraction for strain measurement with a resolution  $\Delta d \sim 10^{-4}$  d  
Microtomography for 3-D imaging of microstructures.

*Other Key Individuals:*

John Kinny	Lawrence Livermore National Laboratory
Richard Ryon	Lawrence Livermore National Laboratory
Ken Skulina	Lawrence Livermore National Laboratory
Cullie Sparks, Jr.	Oak Ridge National Laboratory
Albert C. Thompson	Lawrence Berkeley Laboratory

# MR-CAT

## Materials Research CAT

---

**CAT Director  
and Affiliation****Institutional Affiliations of Participating  
Investigators**

---

Bruce Bunker  
Univ. of Notre Dame  
telephone (219)239-7219  
fax (217)239-5952

Amoco, IIT, Northwestern Univ., Florida Universities, Univ. of Notre Dame

*Discipline:* Materials Time-Resolved Scattering & Spectroscopy, *in-situ* Measurements

*Sector(s):* 1

*Focus:* Investigators in this group have overlapping interests including time-resolved scattering and spectroscopy, spatially resolved measurements, *in situ* measurements, and studies involving elliptically polarized radiation. Research conducted by this CAT will include wide- and small-angle scattering, diffraction, reflectivity, and various spectroscopic studies of phase transitions, disordered systems such as alloys and amorphous materials, organic thin films and self-assembled systems, magnetic materials, fluids, catalysts, polymers, and other condensed-matter systems.

*Key Features:* tapered undulator; multilayer broad-band optics; step-scan and slewing monochromators; dispersive spectroscopy

*Other Key Individuals:*

Pulak Dutta  
John Faber, Jr.  
Timothy Morrison  
Stephen Nagler

Northwestern Univ.  
Amoco  
IIT  
Univ. of Florida

$\mu$ -CAT  
Midwest Universities CAT

CAT Director and Affiliation	CAT Deputy Director and Affiliation	Institutional Affiliations of Participating Investigators
David W. Lynch Iowa State Univ. telephone (515)294-3476 fax (515)294-0689	Alan Goldman Iowa State Univ. telephone (515)294-3585 fax (515)294-0689	Georgia Tech., Iowa State, Kent State, SUNY/Stony Brook, Univ. of Missouri/Columbia, Univ. Nebraska/Lincoln, Univ. of Wisconsin/Madison, Washington Univ.

*Discipline:* Materials Science

*Sector(s):* 1

*Focus:* This group proposes studies in four major areas: magnetic x-ray scattering, surface and interface scattering, microdiffraction, and bulk and surface phase transitions. Magnetic x-ray scattering will be used to study magnetic structures and phase transitions. The surface scattering studies will center on the kinetics and growth of two-dimensional systems, the role of defects in epitaxy, ordered nonepitaxial overlayers, and phase transitions in liquid crystals. Microdiffraction studies will focus on small-grained samples of unusual interest (quasicrystals and mineral particles of extraterrestrial origin).

*Key Features:* 1:1 imaging of undulator A radiation, variable polarization via phase plate, microdiffraction capability, 4-20 keV spectral region

*Other Key Individuals:*

Edward Conrad	GA Inst. of Tech.	Haskell Taub	Univ. of MO/Columbia
H. F. Franzen	Iowa State Univ.	Robert de Angelis	Univ. NE/Lincoln
Clifford Olson	Iowa State Univ.	Peter Stephens	SUNY-Stony Brook
Douglas Robinson	Iowa State Univ.	Thomas Bernatowicz	Washington Univ.
Costa Stassis	Iowa State Univ.	Patrick Gibbons	Washington Univ.
Michael Tringides	Iowa State Univ.	Kenneth Kelton	Washington Univ.
Satyendra Kumar	Kent State Univ.	Michael Winokur	Univ. of WI/Madison
Michael Greenlief	Univ. of MO/Columbia		

# PNC-CAT

## Pacific Northwest Consortium CAT

CAT Director and Affiliation	CAT Deputy Director and Affiliation	Institutional Affiliations of Participating Investigators
Edward A. Stern Univ. of Washington telephone (206) 543-2023 fax (206) 685-0635	E. Daryl Crozier Simon Fraser Univ. telephone (604) 291-4827 fax (604) 291-3592	Battelle-Pacific Northwest Lab., Simon Fraser Univ., The Boeing Co., Univ. of Alberta, Univ. of British Columbia, Univ. of Oregon, Univ. of Saskatchewan, Univ. of Washington, Washington State Univ.

*Discipline:* Environmental Analysis, Materials Research, Macromolecular Crystallography

*Sector(s):* 1

*Focus:* The techniques of spatial and time-resolved XAFS and diffraction (including Laue diffraction), spatial resolved tomography, fluorescence microprobe analysis, surface and interface diffraction, x-ray Raman scattering diffraction, anomalous fine structure, and macromolecular crystallography will be used to study a variety of problems in the environmental and materials sciences areas. Materials research will include fundamental studies, as well as studies relating to the interaction of materials with the environment. Environmental sciences studies involve natural systems that are heterogeneous and complex. Macromolecular crystallography efforts will investigate biological methods of sequestering environmental toxins in addition to basic studies.

*Other Key Individuals:*

**PNC-CAT Executive Board**

E.D. Crozier (Assoc. Dir.)	Simon Fraser Univ.	Bradford B. Pate	Washington State Univ.
Steve Heald	Battelle-Pacific NW Lab	Larry B. Sorensen	Univ. of Washington
Wim Hol	Univ. of Washington	E.A. Stern (Director)	Univ. of Washington
Mike N.G. James	Univ. of Alberta	Ray Stults	Battelle-Pacific NW Lab.
Michael L. Knotek	Battelle-Pacific NW Lab.		

**Other Individuals**

James E. Amonette	Battelle-Pacific NW Lab.	Yanjun Ma	Battelle-Pacific NW Lab.
Donald R. Baer	Battelle-Pacific NW Lab.	Shas V. Mattigod	Battelle-Pacific NW Lab.
Fredrick Brown	Univ. of Washington	Ethan A. Merritt	Univ. of Washington
Robert L. Ingalls	Univ. of Washington	Ronald E. Stenkamp	Univ. of Washington

# SBC-CAT

## Structural Biology Center CAT

---

### CAT Director and Affiliation

Edwin M. Westbrook  
Argonne Natl. Lab.  
telephone (708)252-3983  
fax (708)252-6126  
e-mail: westbrook@anbipc.  
bim.anl.gov

### Institutional Affiliations of Participating Investigators

Argonne Natl. Lab., Brandeis Univ., Cold Spring Harbor Lab., Columbia Univ., Cornell Univ., Genentech, Inc., Univ. of AL-Birmingham, Univ. of Minnesota, Univ. of Washington, Univ. of Wisc.-Madison, Washington Univ., Weizmann Inst. of Science, Yale Univ.

*Discipline:* Structural Biology

*Sector(s):* 1

*Focus:* The scientific focus of the SBC will be macromolecular crystallography. Five principal applications are expected to dominate SBC use: monochromatic data collection from microcrystals; monochromatic data collection from crystals with large cell dimensions; monochromatic data collection from large numbers of closely similar crystal structures; data collection at several discrete energies from a single crystal for use in the multiple-energy anomalous dispersion (MAD) phasing method; and polychromatic (Laue) data collection for either static or kinetic structure analysis.

*Key Features:* Development of detectors; data acquisition, processing, and reduction software; development of experimental methods.

### *Other Key Individuals:*

Leonard J. Banaszak  
Charles E. Bugg  
Steven E. Ealick  
Wayne Hendrickson  
Anthony A. Kossiakoff

University of Minnesota  
Univ. of AL-Birmingham  
Cornell University  
Columbia University  
Genetech, Inc.

F. Scott Mathews  
Ethan A. Merritt  
Ivan Rayment  
Paul Sigler  
Ada Yonath

Washington University  
University of Washington  
Univ. of Wisc.-Madison  
Yale University  
Weizmann Inst. of Science

# SRI-CAT

## Synchrotron Radiation Instrumentation CAT

CAT Director and Affiliation	CAT Deputy Directors and Affiliations	Institutional Affiliations of Participating Investigators
Dennis M. Mills Argonne Natl. Lab. telephone (708)252-5680 fax (708)252-3222	Efim Gluskin Argonne Natl. Lab. telephone (708)252-4788 fax (708)252-3222	Argonne Natl. Lab., Cornell, Exxon, LBL, NIST, Purdue Univ., Stanford Synchrotron Radiation Lab., Univ. of Houston
	Roberto Colella Purdue University telephone (317)494-3029 fax (317)494-0706	

*Discipline:* X-ray Physics and Novel Synchrotron Radiation Instrumentation

*Sector(s):* 3

*Focus:* This CAT will focus on both short- and long-term objectives. Short-term objectives include the development and diagnosis of insertion devices, high-heat-load optics, and other novel techniques, all of which will provide a baseline of operation for the entire community of APS CATs. The long-term objective is the development and implementation of strategic instrumentation programs that will open up new areas of research at the APS. Among the initial strategic instruments to be developed are a millivolt-resolution back-scattering beamline for inelastic scattering, a microvolt-resolution instrument for nuclear-Bragg scattering, a 1-4 keV radiation source and beamline, and a microfocusing optics and techniques beamline.

*Other Key Individuals:*

Ercan Alp	APS/XFD	Daniel Legnini	APS/XFD
Joh R. Arthur	SSRL	Albert T. Macrander	APS/XFD
Lahsen Assoufid	ASP/XFD	Ian McNulty	APS/XFD
Donald Bilderback	CHESS	Tim M. Mooney	APS/XFD
Paul Cowan	ANL/PHY	Simon C. Moss	Univ. of Houston
Roger Dejus	APS/XFD	Robert Popper	APS/XFD
Stepehn Durbin	Purdue Univ.	Kevin Randall	APS/XFD
Patricia Fernandez	APS/XFD	Brian Rodricks	APS/XFD
Dean Haeffner	APS/XFD	C. Shawn Rogers	APS/XFD
Richard C. Hewitt	Exxon	Qun Shen	CHESS
Terrence Jach	NIST	Deming Shu	APS/XFD
Stefan Joksch	APS/XFD	Sunhil K. Sinha	Exxon
Ali Khounsary	APS/XFD	Robert K. Smither	APS/XFD
Szczesny B. Krasnicki	APS/XFD	George Srajer	APS/XFD
Vladimir Kushnir	APS/XFD	Albert C. Thompson	APS/XFD
Tuncer M. Kuzay	APS/XFD	Shenglan Xu	APS/XFD
Barry Lai	APS/XFD	Wenbing Yun	APS/XFD
Wah-Keat Lee	APS/XFD		

# UNI-CAT

## A University-National Laboratory-Industry CAT

---

**CAT Director  
and Affiliation**

Haydn Chen  
Univ. of Ill.  
telephone (217)333-7636  
fax (217)333-2736  
e-mail: profchen@ux1.  
cso.uiuc.edu

**Institutional Affiliations of Participating  
Investigators**

Allied Signal Inc., Allied Signal Res. and Technol., Oak Ridge Natl. Lab.,  
Univ. of Illinois/Urbana-Champaign, UOP Res. Center

*Discipline:* Materials Science, Structural Crystallography, Time-Resolved Studies

*Sector(s):* 1

*Focus:* This group proposes research at the cutting edge of the fields of physics, chemistry, biology, materials science, chemical engineering, polymer sciences, and geology, with an emphasis on projects that are cross-disciplinary in both scientific interest and methodology. Major efforts will be in the areas of macromolecular crystallography, diffuse x-ray scattering, surface/interface diffraction and scattering, millivolt/nanovolt resolution scattering spectroscopy, magnetic x-ray scattering, time-resolved structural scattering, and x-ray absorption spectroscopy.

*Key Features:* Dedicated surface/interface facility including MBE and CVD chambers, time-resolved studies down to nanosecond range, millivolt/nanovolt resolution scattering and spectroscopy.

*Other Key Individuals:*

Howard Birbaum	Univ. of Illinois/U-C	Heinz J. Robota	Allied-Signal Inc.
Robert W. Broach	UOP Research Center	Ian Robinson	Univ. of Illinois/U-C
Tai-chang Chiang	Univ. of Illinois/U-C	Ralph Simmons	Univ. of Illinois/U-C
Hawoong Hong	Univ. of Illinois/U-C	Cullie Sparks	Oak Ridge Natl. Lab.
Gene Ice	Oak Ridge Natl. Lab.	Eliot Specht	Oak Ridge Natl. Lab.
Bennett C. Larson	Oak Ridge Natl. Lab.		



**APPENDIX 2**

**RESEARCH AND DEVELOPMENT PROGRAM**



## RESEARCH AND DEVELOPMENT PROGRAM

### A.1 Introduction

Assuming that the construction of APS Beamline Initiative will begin in FY 1996, the scope of the R&D program has been described in this Appendix. It is clear that much emphasis of this R&D will be on the instrumentation development required in the future. It should be also realized that there are various elements of accelerator systems that will strongly interact with the requirements of the experimental facilities instrumentation and that this R&D is possible in FY 1996 after commissioning of the storage ring.

Many of the components of the experimental facilities in the future will be one of the kind. Hence, extra assurance must be established in the final performance of the facilities through a strong R&D program on all the subcomponents, and such a program should begin very early.

Key R&D items require large amounts of capital funds to implement, and this has been folded in the current planning.

### A.2 Insertion Devices

The uniqueness of the IDs required to meet the future user needs demand an early beginning to R&D studies in the following areas:

- UHV requirements in the straight section in which in-vacuum IDs will be introduced.
- ID baking capabilities and influence on the magnetic performance.
- Capabilities to perform *in situ* magnetic measurements on in-vacuum IDs.
- ID vacuum chamber prototype design for in-vacuum IDs, superconducting IDs, polarization IDs, and multiple-source IDs.
- Influence of new IDs on the storage-ring performance.
- Rf interaction with in-vacuum IDs and unusual ID vacuum chamber geometries.
- Heat loads from the IDs proposed in the new initiative on the storage-ring vacuum chamber.
- Development of new magnet geometries for new IDs.
- R&D to define new devices capable of delivering unique radiation properties.

### A.3 Beamline Front Ends

Anticipated heat loads that will have to be handled by the front-end components on future beamlines demand enhancement of heat transfer capabilities by an order of magnitude. Such requirements can only be met by extensive engineering R&D in developing new heat transfer techniques and through the identification and testing of new materials for these unique applications.

The R&D activities will address the needs of almost all the components of the front ends. The emphasis will be in the following areas:

- Beam stops
- Apertures
- Photon beam position monitors
- Safety shutters
- Windows for beamlines
- Personnel safety and control
- Detailed radiation safety analysis

Because the requirements will widely vary from one front end to another in the future, early beginning of this activity is essential. These activities will use the experience and capabilities gained in developing the beamlines for the current construction project.

#### **A.4 Beamline Components**

This R&D program can simply be divided into the following:

- Radiation physics
- X-ray optics
- Metrology
- Detector development
- Storage Ring Performance

The beamlines to be developed by the SRI CAT (primarily made up of APS Experimental Facilities staff) will provide an environment to perform much of the R&D needed in the above areas. These SRI CAT beamlines will begin their operation during FY 1995-96. The future beamlines are unique and differ from one beamline to the next. However, the R&D requirements share some common needs. They include the R&D on unique radiation properties, high heat load optics, metrology capabilities, beamline controls, detector capabilities, and data acquisition, handling, and analysis. For each of the new IDs the performance of the operation of each of the storage ring components will have to be developed in detail, as will the dynamics of the positron lattice.

#### **A.5 Cost and Schedule for R&D Program and Other Support**

The cost and schedule for accomplishing the R&D work are based on the brief narrative of R&D items identified in this appendix. One of the most important considerations in developing the schedule is the need for a smooth transition from the current construction phase to the R&D phase described here and from the R&D phase to the programmatic operations phase of the added beamlines and other facilities to the APS.

Costs for R&D effort, materials and services, other project costs, and equipment are shown in Table A.1. The other project costs include the cost of operating new facilities provided by this Initiative, programmatic operations costs as the beamlines begin their operation, additional costs for the ES&H effort on the new facilities added by this Initiative, and maintenance costs of the facilities added here. The dollars shown are cost escalated in each fiscal year. The dollar figures shown here are consistent with the Schedule 44 document submitted to the DOE in Jan. 1994.

Table A.1

Effort and Cost for Research and Development Program and Other Project Costs		Effort and Cost for Research and Development Program and Other Project Costs			
Activity	FY1996	FY1997	FY1998	FY1999	
<b>Effort (WTE)</b>					
Accelerator Systems	0	1	1	0	
Controls	0	1	1	0	
Insertion Device Development	2	2	2	3	
Front End Development	2	2	2	3	
X-ray Optics Development	1	2	2	2	
Instrument Development	0	0	1	2	
Detector Development	0	0	1	1	
<b>Effort Total (WTE)</b>	5	8	10	12	
<b>Effort Cost (Escalated in \$K)</b>	700	1,000	350	0	
<b>Materials and Services Cost (Escalated in \$K)</b>	360	590	180	0	
<b>Other Project Costs*</b>	0	0	2,110	4,220	
<b>Capital Equipment Cost (Escalated in \$K)</b>	1,800	1,060	4,230	6,340	
<b>TOTAL COST (Escalated in \$K)</b>	2,860	2,500	6,870	10,560	
* This includes facility operating cost for the items in this initiative, programmatic research costs, ES&H costs, and maintenance costs.					

**APPENDIX 3**  
**COPY OF SCHEDULE 44**



DEPARTMENT OF ENERGY  
FY 1996 FIELD BUDGET PROCESS  
CONSTRUCTION PROJECT DATA SHEETS  
ENERGY SUPPLY RESEARCH AND DEVELOPMENT - PLANT AND CAPITAL EQUIPMENT  
BASIC ENERGY SCIENCES

(Tabular dollars in thousands. Narrative material in whole dollars)

<p>1. Title and Location of Project</p> <p style="text-align: center;">APS Beamline Initiative          Argonne National Laboratory          Argonne, Illinois</p>	<p>2. Project No.</p>	
<p>3a. Date technical work initiated (Title I design start): 1st Quarter FY 1996</p>	<p>5. Previous Construction Cost Estimate: NONE</p>	
<p>3b. Technical Work (Title I &amp; II) duration:</p> <p style="text-align: center;">Conventional Facilities - 6 months</p>		
<p>4a. Date physical construction starts:</p> <p style="text-align: center;">2nd Quarter FY 1996</p>	<p>6. Current Construction Cost Estimate: \$53,000</p>	
<p>4b. Date construction ends:</p> <p style="text-align: center;">4th Quarter FY 1999</p>	<p>Date: December 1993</p> <p>TEC: \$53,000          TPC: \$77,000</p>	

7. Financial Schedule:

Fiscal Year	Appropriations	Obligations	Costs
1996	3,500	3,500	3,000
1998	22,000	22,000	13,500
1997	16,000	16,000	19,200
1999	11,500	11,500	17,300

CONSTRUCTION PROJECT DATA SHEETS

1. Title and Location of Project	APS Beamline Initiative Argonne National Laboratory Argonne, Illinois	2. Project No.
----------------------------------	---	----------------

8. Brief Physical Description of Project

The DOE is constructing a new generation 6-7 GeV Synchrotron Radiation Source known as the Advanced Photon Source (APS) at Argonne National Laboratory (Project No. 89-R-402). This facility, to be completed in FY 1997, is capable of providing 70 x-ray sources of unprecedented brightness to meet the research needs of virtually all scientific disciplines and numerous technologies. The technological research capability of the APS in the areas of energy, communications, and health will enable a new partnership between the DOE and U.S. industry. Current funding for the APS will complete the current phase of construction so that scientists can begin their applications in FY 1997. It is now appropriate to plan to construct a set of beamlines to perform the state-of-the-art x-ray research by the Collaborative Access Teams made up of researchers from universities, federal laboratories, and industry. Comprehensive utilization of the unique properties of APS beams will enable cutting-edge research not currently possible. These beamline facilities will be targeted for the important science/technology goals of the U.S. x-ray community and will be available on a peer-review or proprietary basis to all Collaborative Access Teams.

In this APS Beamline Initiative, 2.5-m-long insertion-device x-ray sources will be built on 4 straight sections of the APS storage ring and an additional 4 bending-magnet sources will also be put in use. The front ends for these 8 x-ray sources will be built to contain and safeguard access to these bright x-ray beams. In addition, funds will be provided to build standard beamline components to meet the scientific and technological research demands of the Collaborative Access Teams.

The following is a brief physical description of the APS Beamline Initiative:

**TECHNICAL COMPONENTS:** The major component for the production of x-rays will be 2.5-m-long insertion devices and bending magnets. The insertion devices will be built on 4 available straight sections of the storage ring and the 4 bending-magnet sources are located between the insertion-device x-ray sources. All these x-ray sources will be contained by front ends consisting of beam stops, safety shutters, filters and radiation windows. The components of beam lines that will be supported as part of the Beamline Initiative will meet the current requirements of users to perform x-ray research investigations. Many of these beamline components, as provided through Collaborative Access Teams, have already been requested by industrial and academic users at the present time.

CONSTRUCTION PROJECT DATA SHEETS

- 
- |                                  |   |                |
|----------------------------------|---|----------------|
| 1. Title and Location of Project | APS Beamline Initiative<br>Argonne National Laboratory<br>Argonne, Illinois | 2. Project No. |
|----------------------------------|---|----------------|
- 

9. Purpose, Justification of Need for, and Scope of Project

The Advanced Photon Source is in great demand by scientific and technological researchers from the field of physics, materials, chemistry, biology, energy, pharmaceuticals, and medicine. The new Beamline Initiative has two main goals: First, to provide standard beamline components to the technological and academic users forming Collaborative Access Teams. Second, to support the unexpected demand for bright x-ray beams by the user community that could not be met in the funded phase of the project.

The APS Beamline Initiative reflects the need for the ultra-bright x-ray beams from industrial and academic users. Applications continue to increase and they span a wide variety of scientific disciplines, for example, from studies of biological cells to structure of drugs to non-invasive diagnostics of the human heart, from physical sciences to environmental sciences.

The importance of this facility for industrial competitiveness of the U.S. is clear. The European countries have jointly built a facility in Grenoble, France, which is similar to the 6-7 GeV Synchrotron Radiation Source being built at Argonne. The Japanese are building a facility in Nishi-Harima which is larger than the APS Project even when the new Beamline Initiative is completed.

CONSTRUCTION PROJECT DATA SHEETS

1. Title and Location of Project	2. Project No.
APS Beamline Initiative Argonne National Laboratory Argonne, Illinois	

10. Details of Cost Estimate: (dollars in thousands)

A. Engineering, design and inspection at 7.90% of construction costs, Item B	\$ 3,290
B. Construction costs of technical components	45,000
C. Contingency	<u>4,710</u>
Total Construction Costs	\$53,000

11. Method of Performance

Customary accepted practice will be followed. The design of technical components will be performed by the Laboratory. To the extent feasible, construction and other procurements will be by means of fixed-price contracts awarded on the basis of competitive bidding.

CONSTRUCTION PROJECT DATA SHEETS

1. Title and Location of Project	2. Project No.
APS Beamline Initiative Argonne National Laboratory Argonne, Illinois	

	FY 96	FY 97	FY 98	FY 99	Total
<b>12. Funding Schedule of Project</b>					
<b>A. Total Project Funding</b>					
<b>1. Total facility costs</b>					
(a) Construction line item	\$3,500	\$22,000	\$16,000	\$11,500	\$53,000
(b) Expense funded equipment	0	0	0	0	
(c) Inventories	0	530	530	0	1,060
<b>2. Other project funding</b>					
(a) R&D necessary to complete construction	1,060	1,590	530	0	3,180
(b) Other project related costs <sup>a/</sup>	1,800	1,060	6,340	10,560	19,760
(c) Conceptual design costs	0	0	0	0	0
Total Project Costs	\$6360	\$25,180	\$23,400	\$20,060	\$77,000

<sup>a/</sup>See Section 12.B for annual operating costs required in FY 2000.

CONSTRUCTION PROJECT DATA SHEETS

1. Title and Location of Project	APS Beamline Initiative. Argonne National Laboratory Argonne, Illinois	2. Project No.
----------------------------------	--	----------------

12. Funding Schedule of Project (contd)

B. Other Related Annual Costs<sup>a/</sup> (estimated life of project: 20 years)

1. Facility Operating Cost	\$ 800
2. Programmatic Research	3,100
3. ES&H Cost	200
4. Maintenance Cost	210
5. Capital Equipment Related to Programmatic Research	<u>8,000</u>
Total Related Annual Costs	\$12,310

<sup>a/</sup>Estimated costs shown are incremental to annual costs shown in Project No. 89-R-402 and are in thousands, escalated to Fiscal Year 2000 dollars.

CONSTRUCTION PROJECT DATA SHEETS

1. Title and Location of Project	2. Project No.
APS Beamline Initiative Argonne National Laboratory Argonne, Illinois	

**13. Narrative Explanation of Total Project Funding and Other Related Funding Requirements**

- A. Total project funding
  - 1. Total Facility costs
    - (a) Construction line item - no narrative required.
    - (b) Inventories
  - 2. Other project funding
    - (a) R&D necessary to complete construction.  
 These costs represent the R&D and capital equipment necessary to assure the best possible performance of the facility, to optimize conceptual engineering designs, and to develop the quality-assurance plans for testing of all hardware. The R&D plan includes development of front-end components and standard components of the beam lines and the optics, which will perform efficiently in handling the radiation power from insertion devices. The state-of-the-art research identified during phase-1 operation will require major R&D to implement instruments during Beamline Initiative.
    - (b) Other project-related costs  
 These costs provide support for staff, utilities, management, start-up, commissioning, operations and operations-related R&D.
- B. Total related funding requirements
  - 1. Facility operating costs - The major elements comprising the facility operating costs are electricity, space and custodial costs, and other service and management effort required to operate the facility.
  - 2. Programmatic Research - Continuing R&D is required to develop standard beam-line components, and safety engineering to provide greater capability to fully implement this scientific resource.
  - 3. ES&H Costs - The additional beam-line facilities will require increased safety coverage.

CONSTRUCTION PROJECT DATA SHEETS

1. Title and Location of Project	2. Project No.
APS Beamline Initiative Argonne National Laboratory Argonne, Illinois	

13. Narrative Explanation of Total Project Funding and Other Related Funding Requirements (contd)

B. Total related funding requirements (contd)

4. Maintenance Costs - Maintenance of the additional user modules and experimental equipment is estimated to increase from approximately 2.5% of the annual operating costs in FY 2000 to approximately 7% of the annual operating cost by FY 2004.
5. Capital Equipment Related to Programmatic Research - The continuing R&D program to improve the quality of the facilities available to scientific users will require adding, upgrading or replacement of scientific equipment.

14. Incorporation of Fallout Shelters

Adequate Argonne fallout-shelter space currently exists in designated fallout-shelter areas. The existing shelters can be augmented by the basement of the control laboratory and office building.

15. Federal Compliance with Pollution-Control Standards

The total cost of this project includes the cost of those measures required to assure compliance with Executive Order 12088. Sanitary waste will be discharged into existing sewers connected to adequate sewage-treatment facilities. Airborne contaminants will be collected and filtered from exhaust air.

16. Evaluation of Flood Hazards

This project will be located in an area not subject to flooding as determined in accordance with Executive Order 11988.

CONSTRUCTION PROJECT DATA SHEETS

---

1. Title and Location of Project	2. Project No.
APS Beamline Initiative Argonne National Laboratory Argonne, Illinois	

---

**17. Environmental Impact**

Beamline of the APS was included within the project conceptual-design basis used for the Environmental Assessment (DOE/EA-0389) for the 6-7 GeV Synchrotron Radiation Source (Project No. 89-R-402). This project complies with all provisions of the National Environmental Policy Act and other related DOE orders and guidelines protecting the environment. Based on the Environmental Assessment (DOE/EA-0389) a Finding of No Significant Impact notice was published in the Federal Register, Vol. 55, No. 95 (5/16/90) for the 6-7 GeV Synchrotron Radiation Source.

**18. Accessibility for the Handicapped**

The project will be accessible to the handicapped in accordance with the Architectural Barriers Act, Public Law 90-480, and implementing instruction in the Federal Property Management Regulations (41 CFR 101.19.6).

**19. Facility Utilization**

See attached.

**20. Safe and Healthful Work Place**

Cost estimates for this project include direct funding of safety-coordination activities required to conduct construction operations consistent with the standards promulgated under Section 19 of the Occupation Safety and Health Act of 1970, Executive Order No. 12196, and related federal regulations. Specific construction of all safety systems as described in the Preliminary Safety Analysis Report for this project approved by DOE in February 1990 are also included in the project estimates. Annual ES&H operating costs are included in the estimate presented in Section 12.3.

**Distribution for ANL-93/18 Rev. 1**

**Internal:**

Y. Cho  
J. Galayda  
D. Getz  
D. Moncton  
G. Shenoy (56)

B. Sproule  
E. Temple  
APS Document Control Center (2)  
TIS Files

**External:**

DOE-OSTI (2)  
DOE Chicago Field Office:  
Manager

University of Chicago Board of Governors for Argonne National Laboratory,  
Committee to Advise the Laboratory Director on APS Construction (7)