

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: GC Acrylic Plastic

SECTION 1- PRODUCT AND COMPANY IDENTIFICATION

Product Type: Specialty
Product Name: **GC ACRYLIC PLASTIC**
Part Number(s): **10-8665**

Emergency Contact: **Chemtrec**
Phone: **(800) 424-9300**

SECTION 2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

OSHA HCS (29 CFR 1910.1200)

Flam. Aerosol 1; Liquefied gas; Eye Irrit. 2; Skin Irrit. 2; STOT SE 3; Asp. Tox. 1

Label elements

Hazard Symbol



Signal word(s)

DANGER

Hazard Statement(s)

Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.
Causes serious eye irritation.
Causes skin irritation.
May cause drowsiness or dizziness.
May be fatal if swallowed and enters airways.

Precautionary Statement(s)

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Wear protective gloves/protective clothing/eye protection/face protection.
Avoid breathing dust/fume/gas/mist/vapours/spray.

Other hazards

Toxic to aquatic life.

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: GC Acrylic Plastic

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredient(s)	% wt. *	CAS No.	Hazard classification
Acetone	20 - 30	67-64-1	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336
Xylene**	20 - 30	1330-20-7	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Eye Irrit. 2B; H319 Asp. Tox. 1; H304 STOT SE 3; H336 Aquatic Acute 2; H401
Propane	10 - 20	74-98-6	Flam. Gas 1; H220 Liquefied gas; H280
Butane	10 - 20	106-97-8	Flam. Gas 1; H220 Liquefied gas; H280
n-Butyl Acetate	5 - 15	123-86-4	Flam. Liq. 3; H226 STOT SE 3; H336
Glycol Ether PM Acetate	1 - 5	108-65-6	Flam. Liq. 3; H226

Additional Information - Substances in the product which may present a health or environmental hazard, or which have been assigned occupational exposure limits, are detailed below.:

- **Contains: Ethylbenzene (CAS No. 100-41-4) <10%; Benzene (CAS No. 71-43-2) <0.1%; and Toluene (CAS No. 108-88-3) <0.5%

* The exact percentage withheld as a trade secret in accordance with 29 CFR 1910.1200.

SECTION 4. FIRST AID MEASURES



Description of first aid measures

Inhalation	Move person to fresh air. If breathing is labored, administer oxygen. If symptoms develop, obtain medical attention.
Skin Contact	Wash affected skin with soap and water. If symptoms develop, obtain medical attention.
Eye Contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.
Ingestion	Do not give anything by mouth to an unconscious person. Seek medical treatment. Do NOT induce vomiting.



1801 Morgan Street
Rockford, IL 61102
Phone: (815) 968-9661
Fax: (815) 968-9731
www.gcelectronics.com

SDS Number: 159
Revision Date: 7/24/2015
Supersedes Date: 1/25/2013

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: GC Acrylic Plastic

SECTION 4. FIRST AID MEASURES (CONTINUED)

Most important symptoms and effects, both acute and delayed	May be harmful if swallowed and enters airways.
Indication of any immediate medical attention and special treatment needed	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media	
-Suitable Extinguishing Media	Extinguish with carbon dioxide, dry chemical, foam or water spray.
-Unsuitable Extinguishing Media	Do not use water jet.
Special hazards arising from the substance or mixture	Highly flammable vapor (flash point below 23°C).
Advice for fire-fighters	A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep containers cool by spraying with water if exposed to fire.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Avoid contact with skin and eyes. Avoid breathing vapors.
Environmental precautions	Avoid release to the environment.
Methods and material for containment and cleaning up	Cover spills with inert absorbent material. Transfer to a container for disposal or recovery.
Reference to other sections	None
Additional Information	None

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling	Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Avoid contact with skin and eyes. Use product in a well-ventilated area only. Avoid breathing spray.
Conditions for safe storage, including any incompatibilities	
-Storage temperature	Keep in a cool, well ventilated place. Store at temperatures not exceeding 50 °C / 122 °F.
-Incompatible materials	This product should be stored away from sources of strong heat or oxidizing chemicals.
Specific end use(s)	Coating

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: GC Acrylic Plastic

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

SUBSTANCE.	CAS No.	(8hr TWA)		(STEL)		Note:
		PEL (OSHA)	TLV (ACGIH)	PEL (OSHA)	TLV (ACGIH)	
Acetone	67-64-1	1000 ppm	500 ppm	-----	750 ppm	^NIC
Propane	74-98-6	1000 ppm	Aspyx.#	-----	-----	#
Ethyl benzene	100-41-4	100 ppm	20 ppm	----	-----	A3
Xylene	1330-20-7	100 ppm	100 ppm	----	150 ppm	----
n-Butyl Acetate	123-86-4	150 ppm	150 ppm	-----	200 ppm	-----

^NIC = Notice of Intended Changes (ACGIH®); #Assure minimum oxygen content of work atmosphere.; A3 - Confirmed Animal Carcinogen (ACGIH).

Recommended monitoring method

NIOSH 1300 (Ketones I); NIOSH 1501 (Hydrocarbons, Aromatic);
 OSHA 1002 (Xylene) NIOSH 1450 (n-Butyl Acetate)

Exposure controls

Appropriate engineering controls

Provide adequate ventilation to ensure that the occupational exposure limit is not exceeded.

Personal protection equipment

Eye/face protection

Wear protective eyewear (goggles, face shield, or safety glasses).



Skin protection (Hand protection/ Other)

Wear suitable gloves if prolonged skin contact is likely (Nitrile rubber or Butyl rubber). Use gloves only once. Check with protective equipment manufacturer's data.



Respiratory protection

Normally no personal respiratory protection is necessary. In case of insufficient ventilation, wear suitable respiratory equipment. Check with protective equipment manufacturer's data.



Thermal hazards

Not normally required. Use gloves with insulation for thermal protection, when needed.

Environmental Exposure Controls

Prevent liquid entering sewers, basements and work pits.



1801 Morgan Street
Rockford, IL 61102
Phone: (815) 968-9661
Fax: (815) 968-9731
www.gcelectronics.com

SDS Number: 159
Revision Date: 7/24/2015
Supersedes Date: 1/25/2013

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: GC Acrylic Plastic

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Aerosol spray
Color	Clear
Odor	Hydrocarbon
Odor Threshold (ppm)	Not available
pH (Value)	Not available
Melting Point (°C) / Freezing Point (°C)	Not available
Boiling point/boiling range (°C):	Not available
Flash Point (°C)	Not available
Evaporation Rate	Not available
Flammability (solid, gas)	Extremely flammable aerosol.
Explosive Limit Ranges	2.1% - 9.5% v/v (Propane)
Vapor pressure (Pascal)	ca. 95×10^4 (Propane)
Vapor Density (Air=1)	ca. 1.56 @ 0°C (Propane)
Density (g/ml)	Not available
Solubility (Water)	Not available
Solubility (Other)	Not available
Partition Coefficient (n-Octanol/water)	Not available
Auto Ignition Point (°C)	Not available
Decomposition Temperature (°C)	Not available
Kinematic Viscosity	<20 mm ² /s @ 40°C
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Other information	Not available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	Stable under normal conditions.
Chemical stability	Stable.
Possibility of hazardous reactions	None anticipated.
Conditions to avoid	Avoid contact with heat and ignition sources.
Incompatible materials	Strong oxidizing agents
Hazardous decomposition product(s)	Carbon monoxide, Carbon dioxide, Acrid smoke



1801 Morgan Street
Rockford, IL 61102
Phone: (815) 968-9661
Fax: (815) 968-9731
www.gcelectronics.com

SDS Number: 159
Revision Date: 7/24/2015
Supersedes Date: 1/25/2013

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: GC Acrylic Plastic

SECTION 11. TOXICOLOGICAL INFORMATION

Exposure routes: Inhalation, Skin Contact, Eye Contact

Information on toxicological effects

Acetone (CAS No. 67-64-1)

Acute toxicity

Oral LD50 = 5800 mg/kg (rat)
Dermal LD50 >15800 mg/kg (rabbit)
Inhalation LC50 76 mg/L (4 hour(s)) (rat) - Vapours may cause drowsiness and dizziness.

Irritation / Corrosivity

Causes serious eye irritation. Repeated exposure may cause skin dryness or cracking.

Sensitisation

It is not a skin sensitiser.

Repeated dose toxicity

Oral NOAEL = 900 mg/kg/day (rat) (90-days)
Inhalation NOAEL \geq 19,000 ppm (rat)

Carcinogenicity

It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

Mutagenicity

Negative

Toxicity for reproduction

Negative

Other information

None known.

Xylenes (CAS No.1330-20-7)

Acute toxicity

Oral LD50 = 3520 mg/kg (rat)
Dermal LD50 >5000 mg/kg (rabbit)
Inhalation LC50 = 27.6 mg/L (4 hour(s)) (rat) - Vapours may cause drowsiness and dizziness. May cause respiratory irritation.

Irritation / Corrosivity

Causes eye irritation. Causes skin irritation. Repeated exposure may cause skin dryness or cracking.

Sensitisation

It is not a skin sensitiser.

Repeated dose toxicity

Oral NOAEL = 900 mg/kg/day (rat) (90-days)
Inhalation NOAEL \geq 19,000 ppm (rat)

Carcinogenicity

It is unlikely to present a carcinogenic hazard to man.*

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

Mutagenicity

Negative

Toxicity for reproduction

Negative

Other information

* Contains: Ethylbenzene (CAS# 100-41-4). A3 - Confirmed Animal Carcinogen with unknown relevance to humans (ACGIH®). IARC Group 2B - Possibly carcinogenic to humans.



1801 Morgan Street
 Rockford, IL 61102
 Phone: (815) 968-9661
 Fax: (815) 968-9731
 www.gcelectronics.com

SDS Number: 159
 Revision Date: 7/24/2015
 Supersedes Date: 1/25/2013

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: GC Acrylic Plastic

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Xylene (CAS No. 1330-20-7)

Acute toxicity	LC50 (96 hour) = 2.6 mg/l (<i>Oncorhynchus mykiss</i>) IC50 (24 hour(s)) = 1 mg/l (<i>Daphnia magna</i>) EC50 (73 hour(s)) = 1.9 mg/l (<i>Pseudokirchnerella subcapitata</i>)
Long Term Toxicity	NOEC (56 days) > 1.3 mg/l (<i>Oncorhynchus mykiss</i>) NOEC (7 days) 1.17 mg/l (<i>Ceriodaphnia dubia</i>) NOEC (73 hours) 1.9 mg/l (<i>Pseudokirchnerella subcapitata</i>)
Persistence and degradability	Readily biodegradable.
Bioaccumulative potential	The product has no potential for bioaccumulation.
Mobility in soil	The product has high mobility in soil.
Results of PBT and vPvB assessment	Not classified as PBT or vPvB.
Other adverse effects	None known.

SECTION 13. DISPOSAL CONSIDERATIONS

Waste treatment methods	Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice.
--------------------------------	--

SECTION 14. TRANSPORT INFORMATION

	<u>U.S. DOT</u>	<u>Sea transport (IMDG)</u>	<u>Air transport (ICAO/IATA)</u>
UN number	1950	1950	1950
Proper Shipping Name	Aerosols, flammable	Aerosols, flammable	Aerosols, flammable
Transport hazard class(es)	2.1	2.1	2.1
Packing group	Not applicable	Not applicable	Not applicable
Environmental hazards	None assigned	None assigned	None assigned
Special precautions for user	None assigned	None assigned	None assigned
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable			



1801 Morgan Street
Rockford, IL 61102
Phone: (815) 968-9661
Fax: (815) 968-9731
www.gcelectronics.com

SDS Number: 159
Revision Date: 7/24/2015
Supersedes Date: 1/25/2013

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: GC Acrylic Plastic

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):

Chemical Name	CAS No.	Typical %wt.	RQ (Pounds)
Acetone	67-64-1	20 - 30	5000
Xylene	1330-20-7	20 - 30	100
Ethyl benzene	100-41-4	2 - 3	1000
n-Butyl Acetate	123-86-4	5 - 15	5000

SARA 311/312 - Hazard Categories:

Fire Sudden Release Reactivity Immediate (acute) Chronic (delayed)

SARA 313 - Toxic Chemicals (40 CFR 372):

Chemical Name	CAS No.	Typical %wt.
Xylene	1330-20-7	20 - 30
Ethyl benzene	100-41-4	2 - 3

SARA 302 - Extremely Hazardous Substances(40 CFR 355):

Chemical Name	CAS No.	Typical %wt.	TPQ (pounds)
None	----	----	----

California Proposition 65 List:

Chemical Name	CAS No.	Type of Toxicity
Toluene*	108-88-3	Developmental, Female Reproductive
Ethyl benzene	100-41-4	Cancer
Benzene*	71-43-2	Cancer; Female Reproductive

*Trace to none.

SECTION 16: OTHER INFORMATION

Hazard Statement(s) and Risk Phrases Listed in: SECTION 3:

Hazard Statement(s)

- H220: Extremely flammable gas.
- H225: Highly flammable liquid and vapor.
- H226: Flammable liquid and vapour.
- H280: Contains gas under pressure; may explode if heated.
- H304: May be fatal if swallowed and enters airways.
- H315: Causes skin irritation.
- H319: Causes serious eye irritation.
- H332: Harmful if inhaled.
- H336: May cause drowsiness or dizziness.
- H373: May cause damage to organs through prolonged or repeated exposure.

- H401: Toxic to aquatic life.
- H412: Harmful to aquatic life with long lasting effects.

Training advice: None.



1801 Morgan Street
Rockford, IL 61102
Phone: (815) 968-9661
Fax: (815) 968-9731
www.gcelectronics.com

SDS Number: 159
Revision Date: 7/24/2015
Supersedes Date: 1/25/2013

SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Product Name: GC Acrylic Plastic

SECTION 16: OTHER INFORMATION (CONTINUED)

GC Electronics believes that the information contained herein is accurate and reliable as of the date of this material safety data sheet, but no representation guarantee or warranty, express or implied, is made as to the accuracy, reliability or completeness of the information. Persons receiving information are encouraged to make their own determination as to the information's suitability and completeness for their particular application.

NO INFORMATION CONTAINED HEREIN CONSTITUTES A PRODUCT WARRANTY OF ANY KIND, WHETHER EXPRESS OR IMPLIED; AND ALL IMPLIED WARRANTIES OF MERCHANT ABILITY AND OF FITNESS FOR A PARTICULAR PURPOSE ARE HEREBY DISCLAIMED BY GC ELECTRONICS.