



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

LUBRIPLATE DS-ES LUBRICANT

LUBRIPLATE DS-ES Lubricant is developed specifically for the electrical and electronics industry. LUBRIPLATE DS-ES Lubricant is being used extensively in automotive switches and contact units where performance is exceeding all of the new safety standards set for this equipment.

LUBRIPLATE DS-ES Lubricant is also highly recommended as a bearing lubricant for electrical motors, spindles and other mechanical devices where low torque, high speeds and long life are essential. Due to the aniline point of this product, seal compatibility is excellent.

LUBRIPLATE DS-ES Lubricant is recommended in the Automotive Industry by these specifications or part numbers:

Chrysler/AMC	MS-3701
	MS-8677
Ford Motor Company	ESB-MIC-158-A
Delco-Remy Div., General Motors	5384-011
ITT Automotive Electrical Products	1502-20007-D116
Saginaw Steering Gear Div.,	
General Motors	7809811
	7813685
	7826313
White Truck Group	16109-5002

LUBRIPLATE DS-ES Lubricant is recommended for:

Battery Posts - Head Lamps - Tail Lamps
Electrical Harness Plug Assemblies
Backup Lamp Connector Sockets
Electrical Switch Contacts - Radio Antenna Assemblies
Aircraft Switch Assemblies
High Voltage Breaker Assemblies
Connectors in the Primary Circuit of Solid-State Ignition

Advantages

- Exceptional oxidation resistance for extended operating life.
- Low Torque start-up capabilities especially in cold weather conditions.
- Excellent metal, rubber, and plastic compatibility.

(over)

Typical Tests

Type of Thickener	Lithium
Worked Penetration @ 77°F	310 to 340
NLGI No.	1
ASTM Dropping Point	360°F/182°C
Mineral Oil Viscosity	
SUS @ 100°F	200
cSt @ 40°C	39
Aniline Point	219
Norma Hoffman Oxidation Bomb Test	3 psi Max./1,000 Hrs.

Packaging Available

Carton 24/14 oz. Cans
Carton 6/6 lb. Cans
35 lb. Pail
120 lb., Quarter Size, Drum
410 lb., Full Size, Drum
Carton 36 - 1¾ oz. Tubes (1x6)

Part No.

L0137-001
L0137-006
L0137-035
L0137-039
L0137-040
L0137-086



Lubriplate Lubricants Company

144 Years of Continuous Lubrication Innovation



RoHS Declaration of Conformity

We, Fiske Brothers Refining Company, declare under our sole responsibility that the following products supplied to our customer are in compliance with the EU RoHS 2 Recast Directive 2011/65/EU.

Part No. L0137-, Lubriplate DS-ES

Iliana Vargas – Associate Technical Director

Name

February 26, 2014

Date

Iliana Vargas

Authorized Signature

FISKE BROTHERS REFINING COMPANY d/b/a LUBRIPLATE LUBRICANTS COMPANY

Manufacturers of Lubricants for the Industrial, Food, Beverage, Pharmaceutical, Automotive and Marine Industries since 1870



Corporate Headquarters: 129 Lockwood Street / Newark, NJ 07105 / Tel: 973-589-9150 / Fax: 973-589-4432
Midwest Office and Plant: 1500 Oakdale Avenue / Toledo, OH 43605 / Tel: 419-691-2491 / Fax: 419-693-3806
www.lubriplate.com / e-mail: info@lubriplate.com





Lubriplate Lubricants Company

144 Years of Continuous Lubrication Innovation



REACH COMPLIANCE

September 22, 2014

Fiske Brothers Refining Company certifies that the product (s) listed below are compliant with the European Union Regulation (EC) 1907/2006, REACH.

None of the ingredients named on the SVHC (Substances of Very High Concern) list to date are used in the manufacturing or formulation of the product.

Product:

Lubriplate DS-ES, Part No. L0137-

Sincerely,

Fiske Brothers Refining Company
d/b/a Lubriplate Lubricants

Iliana Vargas
Associate Technical Director

FISKE BROTHERS REFINING COMPANY d/b/a LUBRIPLATE LUBRICANTS COMPANY

Manufacturers of Lubricants for the Industrial, Food, Beverage, Pharmaceutical, Automotive and Marine Industries since 1870



Corporate Headquarters: 129 Lockwood Street / Newark, NJ 07105 / Tel: 973-589-9150 / Fax: 973-589-4432
Midwest Office and Plant: 1500 Oakdale Avenue / Toledo, OH 43605 / Tel: 419-691-2491 / Fax: 419-693-3806
www.lubriplate.com / e-mail: info@lubriplate.com

